


JKL LAMP PART NO.	COLOR GREEN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) (AVG.)
BF20100-11B	x = 0.318±0.03 y = 0.556±0.03	780 @ 0°C	260	5	40,000 REF.	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>						
					TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>								
<b>A</b> DIMENSION CHANGES RELEASE			DRAWN BY L. WENGSTROM		APPVD BY DATE J.K. 3/15/04		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF20100-11B</b>				
					- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>	RELEASED DATE <b>3/10/04</b>	REVISION DATE <b>3/15/04</b>	REV. NO. <b>A</b>	SHEET <b>1 OF 1</b>		
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE											