



JKL LAMP PART NO.	COLOR WHITE 6900°KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20125-28B	x = .325 y = .295	700 @ 0°C	280	5	38,000 TYP.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>			<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>		<p>JKL COMPONENTS CORPORATION</p>					
					<p>TITLE</p> <p>MINIATURE COLD CATHODE FLUORESCENT LAMP</p>					
<p>DRAWN BY</p> <p>L. WENGSTROM</p>			<p>APPV'D BY</p> <p>L.R.</p>		<p>DATE</p> <p>7/30/09</p>		<p>SIZE</p> <p>A</p>	<p>FSCM NO.</p> <p>55335</p>	<p>DRAWING NO.</p> <p>BF20125-28B</p>	
<p>APPV'D DATE</p> <p>4/22/04</p>			<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>		<p>SCALE</p> <p>NONE</p>		<p>RELEASED DATE</p> <p>4/22/04</p>	<p>REVISION DATE</p> <p>7/30/09</p>	<p>REV. NO.</p> <p>A</p>	<p>SHEET</p> <p>1 OF 1</p>
<p>REV. NO.</p> <p>A</p>	<p>DESCRIPTION/ECO NUMBER</p> <p>RELEASE & CANCEL P-0404-14</p>									