



JKL LAMP PART NO. (REF.)	COLOR WHITE 4200°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20137-26B	x = .372 y = .371	1125 @ 0°C	320	5	42,000 ± 15%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>		<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>		<p>JKL COMPONENTS CORPORATION</p>			
				<p>TITLE</p> <p>MINIATURE COLD CATHODE FLUORESCENT LAMP</p>			
<p>DRAWN BY</p> <p>L. WENGSTROM</p>		<p>APPVD BY</p> <p>L.R.</p>		<p>DATE</p> <p>7/30/09</p>		<p>SIZE</p> <p>A</p>	
<p>RATED LIFE HRS MINIMUM</p> <p>20,000</p>		<p>RELEASE AND CANCEL P-0310-09</p>		<p>FSCM NO.</p> <p>55335</p>		<p>DRAWING NO.</p> <p>BF20137-26B</p>	
<p>REV. NO.</p>		<p>DESCRIPTION/ECO NUMBER</p>		<p>APPVD DATE</p>		<p>SCALE</p> <p>NONE</p>	
		<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>		<p>RELEASED DATE</p> <p>2/23/05</p>		<p>REVISION DATE</p> <p>7/30/09</p>	
				<p>REV. NO.</p> <p>A</p>		<p>SHEET</p> <p>1 OF 1</p>	