



JKL LAMP PART NO.	COLOR WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20170-38B	x = 0.356±0.02 y = 0.326±0.02	1000 @ 0°C	400	5	35,000 TYP.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

NOTE 1: MERCURY (Hg) CONTENT: 2.4mg/LAMP MAX.

 THIRD ANGLE PROJECTION	METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION			
	TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP				
DRAWN BY L. WENGSTROM	APP'VD BY L.R.	DATE 7/30/09	SIZE A	FSCM NO. 55335	DRAWING NO. BF20170-38B
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 12/15/04	REVISION DATE 7/30/09
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	REV. NO.	A	SHEET 1 OF 1

A	RATED LIFE HRS MINIMUM	7/30/09
	RELEASE & CANCEL P-0410-02	12/15/04
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE