

JKL PART NUMBER	LENGTH A +/- 2mm	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF6165-40B	165mm	COOL	600	255	5±1	2,500	20,000
BF6178-40B	178mm	WHITE	650	270	5±1	2,500	20,000

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0		COMPONENTS CORPORATION					TION
			THIRD ANGLE								ION
			PROJECTION DRAWN BY L. WENGSTROM		DATE 27/00	SIZE	FSCM NO.	DRAWING	F 6-40B		
REV. NO.	RELEASED DESCRIPTION/ECO NUMBER	11/27/00 APPV'D DATE	- CAD D MANUAL REVISIO	RAWING - NS NOT PERMI		SCALE	•	RELEASED DATE 11/27/00	REVISION DATE	REV. NO.	SHEET 1 OF 1