



JKL PART NUMBER	- A - LENGTH	COLOR 5000 °k	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
CF26346-37B	346±3.0	x = .345±.01 y = .360±.01	1450	700	6± 1	36,000±15%	40,000
CF26397-37B	397±3.0		1520	725			
CF26448-37B	448±3.0		1820	870			
CF26499-37B	499±3.0		2100	1000			
CF26550-37B	550±3.0		2270	1100			
CF26600-37B	600±3.0		2340	1125			

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		<h1>JKL COMPONENTS CORPORATION</h1>						
		THIRD ANGLE PROJECTION		<b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>						
DRAWN BY <b>L. WENGSTROM</b>		APPV'D BY DATE <b>J.K. 11/18/04</b>		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>CF 26-37B</b>				
CHANGE LENGTH & PART NO. RELEASE & CANCEL P-0410-05		11/18/04 11/17/04		<b>- CAD DRAWING -</b>		SCALE <b>NONE</b>	RELEASED DATE <b>11/17/04</b>	REVISION DATE <b>11/18/04</b>	REV. NO. <b>A</b>	SHEET <b>1</b> OF <b>1</b>
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	MANUAL REVISIONS NOT PERMITTED							