


JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
SM0620S	6.0	.020	.024	0.30	5,000	C-6
SM0640S	6.0	.040	.048	0.60	5,000	C-2V
SM1220S	12.0	.020	.032	0.40	5,000	C-2V
SM1240S	12.0	.040	.088	1.11	5,000	C-2V
SM1250S	12.0	.050	.159	2.00	5,000	C-2V
SM2420S	24.0	.020	.064	0.80	5,000	C-2F
SM2430S	24.0	.030	.159	2.00	5,000	C-2F
SM2440S	24.0	.040	.239	3.00	5,000	C-2F
SM2450S	24.0	.050	.279	3.51	5,000	C-2F
SM2850S	28.0	.050	.279	3.51	5,000	C-2F
SM3020S	30.0	.020	.104	1.31	5,000	C-2F
SM3040S	30.0	.040	.287	3.61	5,000	C-2F
SM3620S	36.0	.020	.143	1.80	5,000	C-2F
SM4820S	48.0	.020	.127	1.60	5,000	CC-2F
SM6020S	60.0	.020	.191	2.40	5,000	CC-2F

		METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- ANGLE +/- 0		JKL COMPONENTS CORPORATION			
		DRAWN BY		APPVD BY DATE		SIZE	FSCM NO.	DRAWING NO.	
		L. WENGSTROM		QC 8/16/00		A	55335	SLIDE BASE SHORT LILIPUT T5.5K	
RELEASED		8/16/00		- CAD DRAWING -		SCALE	RELEASED DATE	REVISION DATE	REV. NO.
		APPVD DATE		MANUAL REVISIONS NOT PERMITTED		NONE	8/16/00		1 OF 1