

LC1-TAPE LENSES FOR CREE XR-E LEDs



- Specially designed for Cree XLAMP XR-E series of LEDs.
- Designed to have uniform white or warm white illumination.
- Lens and Holder material PC allows to use higher temperatures on a printed circuit board (120°C/248°F).
- Best available optical efficiency, more than 90%, with an extremely good cutoff of light
- Integrated holder. Fastening to heat sink with a PU foam adhesive tape of automotive grade
- Please check fastening details from this link:
(http://www.ledil.com/datasheets/DataSheet_TAPE.pdf)


LENS TYPES

NAME	ORDERING CODE	FWHM Angle
LC1-TAPE REAL SPOT	FA10653 LC1-RS	±3°
LC1-TAPE DIFFUSER	FA10655 LC1-D	±5°
LC1-TAPE MEDIUM /DIFFUSER	FA11373 LC1-MD	±12°
LC1-TAPE MEDIUM	FA10652 LC1-M	±14°
LC1-TAPE MEDIUM ver.2	FA11449 LC1-M2	Coming soon
LC1-TAPE OVAL	FA11105 LC1-O-90	±5° x ±21°
LC1-TAPE RECTANGULAR	FA10654 LC1-REC	±11° x ±21°
LC1-TAPE WIDE	FA11045 LC1-W	±27°


© Ledil Oy – PRELIMINARY - Subject to change without prior notice

MEASUREMENT DATA

Relative Intensity LC1-RS




Relative Intensity of FA10810_LC1-D




© Ledil Oy – PRELIMINARY - Subject to change without prior notice

Relative Intensity of FA11373_LC1-MD-Tape




Relative Intensity of LC1-M




© Ledil Oy – PRELIMINARY - Subject to change without prior notice

Relative Intensity of LC1-REC




Relative Intensity of FA11104_LC1-O-90




© Ledil Oy – PRELIMINARY - Subject to change without prior notice

Relative Intensity of FA11045_LC1-W-Tape



EULUMDAT & IES FILES AVAILABLE BY REQUEST

DRAWINGS



© Ledil Oy - PRELIMINARY - Subject to change without prior notice