

### **SPECIFICATION:**

**MATERIAL** 

BLACK PLASTIC: ABS PLASTIC, SICOFLEX, UL 94 V-0

METALIZED

PLASTIC: NICKEL OVER COPPER PLATING


TEMP RATING: -55°C to +125°C

## **BACKSHELL KIT INCLUDES:**

- (2) BACKSHELL HALVES
- (4) MOUNTING SCREWS
- (1) STRAIN RELIEF CLAMP
- (2) STRAIN RELIEF SCREWS

DIMENSIONS (IN.)									
No. OF PINS	Α	В	С	D	E				
09	1.740	0.606	0.984	1.299	0.354				
15	1.740	0.606	1.312	1.626	0.394				
25	1.740	0.606	1.852	2.165	0.433				
37	1.740	0.606	2.500	2.815	0.433				

RoHS COMPLIANT





	<del></del>	<del></del> -	 <b>-`</b>
SERIES -			
POSITIONS —			
009			
015			
025			
037			
MATERIAL			
010 = PLASTIC			
020 = METALIZED PLAST	ΓIC		
RoHS COMPLIANT ——			<b>」</b>
R = HIGH TEMP. PROCE	SS		
COLOR —			
01 = BLACK			
12 = METAL(IZED)			
PUT-UP			
1 = KIT			


#### DO NOT SCALE FROM DRAWING


		DWG NO.		YYYF		
NIORC	omo	SCALE: <b>1:1</b>	SHEET	0F <b>1</b>	2	REV
MANUFACTUR	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NOrComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	CHECKED:		DATE:		
ARE THE PE SHALL NOT		DRAWN: C. SMITH		DATE:	04-10-07	
			m-70000	usi		


# CABLE CLAMPS ORDERED SEPARATELY
















0.421


0.315











P/N 955-09-SR-4-7 CABLE RANGE = 0.157 - 0.276

P/N 955-15-SR-7-10 CABLE RANGE = 0.276 - 0.394

P/N 955-25-SR-9-12 CABLE RANGE = 0.354 - 0.472

P/N 955-37-SR-11-14 CABLE RANGE = 0.433 - 0.551

## DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
C. SMITH
CHECKED:
DATE:

DATE:

NorComp

SCALE: SHEET OF 2 2

DWG NO. 955-YYY-YYYRYY1

REV

3

ROHS COMPLIANT