DESCRIPTION: 0.900 CENTER DUAL PORT D-SUB - FEMALE OVER FEMALE

25 PIN SHOWN

	DIMENSIONS (IN.)			
	9	15	25	37
A	1.204	1.535	2.078	2.724
B	0.984	1.312	1.850	2.500
C	0.494	0.494	0.494	0.494







RECOMMENDED PCB LAYOUT

SPECIFICATION:

MATERIAL:

SHELL:	STEEL, NICKEL PLATED
INSULATOR:	UL 94V-0 RATED, BLACK PA9T, 260° PROCESS TEMP.
CONTACTS:	BRASS
CONTACT PLATING:	GOLD PLATED ENTIRE CONTACT

ELECTRICAL:

INSULATOR RESISTANCE:	1,000 Ohms Min.
DIELECTRIC STRENGTH:	1,000VAC RMS
CURRENT RATING:	5 AMPS
OPERATING TEMPERATURE:	-55° C TO 105° C

179-YYY-513R481

SERIES

POSITIONS
- 009
- 015
- 025
- 037

GENDER
- 31 = FEMALE OVER MALE
- 41 = MALE OVER FEMALE
- 51 = FEMALE OVER FEMALE
- 61 = MALE OVER MALE

SHELL PLATING
- 3 = NICKEL

RoHS COMPLIANT (HIGH TEMP. PROCESS)

HARDWARE OPTIONS
- 48 = 4-40 STAND OFFS/METAL BRACKET

PLATING OPTIONS
- 1 = GOLD FLASH

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: C. SMITH	DATE: 03-30-07		
CHECKED:	DATE:		
SCALE: 1 : 1	SHEET 1 OF 1	REV 4	
DWG NO. 179-YYY-513R481			

NorComp

RoHS COMPLIANT