



SIGN	DATE	DESCRIPTION	APPROVER



- Material**
- Contact pin: Brass
 - Surface of solder tail: Tin plated
 - Insulator (housing): Thermoplastic (UL94V-0)
- Electrical**
- Voltage rating: 300VAC
 - Current rating: 15A
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -30°C to +105°C
 - Soldering temperature: 250°C±10°C/5 Sec
 - Safety approval: (cULus) pending
- RoHS Compliant

N= Number of poles

P.C.B LAYOUT



PART NUMBER:

OSTVFXX5051

No. of Poles		COLOR
04: 2x02 Poles		0: Black
06: 2x03 Poles		5: Green (Standard)
:		6: Blue
48 2x24 Poles		8: Grey

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.



TITLE		OSTVF-5.08mm Series open right-angle 2x2p-2x24p				
PART NO.		OSTVFXX5051		DWG NO.		OSTVFXX5051.DWG
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
Shi Jun 2006.11.07	Marvin 2006.11.07	Marvin 2006.11.07	Marvin 2006.11.07			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
SHEET: 01/01				UNIT: mm	SCALE: NONE	
				REV: C		