



- Material:
- Terminal body : Steel stamping clamp Zinc plated
 - Firm wire chunk : Steel Zinc plating
 - Terminal screw: Steel Zinc plating "-" slot type.
 - Female contact: PhBz(CuSn),Tin plated
 - Terminal top housing: Thermoplastic (UL94V-0)
 - Terminal down housing: Thermoplastic (UL94V-0)

- Electrical: cULus
- Voltage rating: 300V
 - Current rating: 10A
 - Wire range:
 - Solid wire(AWG): 16-28
 - Stranded wire(AWG): 16-28
 - Torque: 1.7 Lb-In.
 - Screw: M2
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Safety Approval: RoHS Compliant

PART NUMBER:

OSTVMXX3550

- | | |
|--------------|---------------------|
| No. of Poles | COLOR |
| 02 2 Poles | 0: Black |
| 03 3 Poles | 5: Green (Standard) |
| | 6: Blue |
| 24 24 Poles | 8: Gray |

POLE		2	3	4	5	6	7	8	9	10	11	12
Dim.L		8.42	12.23	16.04	19.85	23.66	27.47	31.28	35.09	38.90	42.71	46.52
Dim.P		3.81	7.62	11.43	15.24	19.05	22.86	26.67	30.48	34.29	38.10	41.91
Tol.		±0.20					±0.25					
POLE	13	14	15	16	17	18	19	20	21	22	23	24
Dim.L	50.33	54.14	57.95	61.76	65.57	69.38	73.19	77.00	80.81	84.62	88.43	92.24
Dim.P	45.72	49.53	53.34	57.15	60.96	64.77	68.58	72.39	76.20	80.01	83.82	87.63
Tol.		±0.30					±0.40					



TITLE	OSTVM 3.81mm W/O Flange Series												
PART NO.	OSTVMXX3550						DWG NO.	OSTVMXX3550.DWG					
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.									
		Kind 2009.08.22	Kind 2009.08.22		UNIT: mm	Tolerance							
				SHEET: 01/01	SCALE: NONE	X.	±0.50						
				REV: D	X.XX	±0.30							
					X.XX	±0.10							
					X°	±1°							