




SIGN	DATE	DESCRIPTION	APPROVER

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!




SPECIFICATIONS
VOLTAGE & CURRENT: 300 V, 20 A
WITHSTANDING VOLTAGE: AC 2000 V/Min
INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V
TEMPERATURE RANGE: -40 °C ~ +105 °C
SCREW TORQUE VALUE: 12Lb-In.
WIRE RANGE: 22 - 12 AWG
1) MOLDED PARTS: THERMOPLASTIC, UL 94 V-0 BLACK
2) TERMINAL: BRASS, 0.8t, Tin PLATED
3) TERMINAL SCREWS: STEEL, Ni PLATED, M3.5
APPROVAL:
 RoHS Compliant



PART NUMBER: OSTYK601XX030

NO. OF POLES
 02: 2 POLES
 03: 3 POLES
 04: 4 POLES
 ⋮
 30: 30 POLES

N=Number of poles



P.C.B LAYOUT

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.



TITLE OSTYK-601 Without Flange& Cover Series		DWG NO. OSTYK601XX030.DWG	
PART NO. OSTYK601XX030	CHECKED Seamus 2007.07.18	DESIGNED LUCY 2007.7.18	DRAWN LUCY 2007.7.18
APPROVED Shi Jun 2007.07.18	CUST NO.	UNIT: mm	Tolerance
		SCALE: NONE	X. ±0.50
		SHEET: 01/01	X.X ±0.30
		REV.: B	X.XX ±0.10
			X° ±1°