



SIGN	DATE	DESCRIPTION	APPROVER
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

**SPECIFICATIONS**

VOLTAGE & CURRENT: 300 V, 25 A

WITHSTANDING VOLTAGE: AC 2000 V/Min

INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V

TEMPERATURE RANGE: -40 °C ~ +105 °C

SCREW TORQUE VALUE: 8.8 Lb-In.

WIRE RANGE: 22 - 12 AWG

1) MOLDED PARTS: THERMOPLASTIC, UL 94 V-0 BLACK

2) TERMINAL: BRASS, 0.8t, Tin PLATED

3) TERMINAL SCREWS: STEEL, Ni PLATED, M3.5

APPROVAL:   
 RoHS Compliant

PART NUMBER: **OSTYK613XX330**

NO. OF POLES

02: 2 POLES

03: 3 POLES

04: 4 POLES

30: 30 POLES

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

<b>ON-SHORE TECHNOLOGY, INC.</b>		TITLE		OSTYK-613 With Flange Series	
		PART NO.		OSTYK613XX330	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.
Shi Jun 2007.07.18		Seamus 2007.07.18	LUCY 2007.7.18	LUCY 2007.7.18	
SHEET: 01/01		UNIT: mm		Tolerance	
REV.: B		SCALE: NONE		X. ±0.50	
				X.X ±0.30	
				X.XX ±0.10	
				X° ±1°	