

SPECIFICATIONS				
PARAMETERS	VALUES	UNIT		
DIRECTIVITY	OMINI	-		
SENSITIVTY	-45 ± 3	dB		
STANDARD OPERATING VOLTAGE	2	Vdc		
MAX OPERATING VOLTAGE	10	Vdc		
CURRENT CONSUMPTION (MAX)	0.5	mA		
IMPEDANCE	2.2	KOhm		
SIGNAL TO NOISE RATIO (MIN.)	60	dB		
TERMINAL	SOLDER PADS	-		
INTERNAL CAPACITOR	N/A	pF		


THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. LS PROHIBITED.

©2003, Projects Unlimited Inc.

REVISION HISTORY					
LTR	DESCRIPTION	DATE	APPROVED		
-	RELEASED FROM ENGINEERING	1/24/2006			
Α	ADDED TERMINAL POLARITY	2/5/2007	D.F.		
В	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	10/26/2010	B.R.		







## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

JNLESS OTHERWISE		Designed by	Date	Checked by	Date	Α
SPECIFIED:	SIZE	J.A.F.	1/24/2006	B.R.	1/24/2006	
MILLIMETERS,  TOLERANCES ARE ±0.5 AND	A3	pui.			TO	1
ANGLES ARE ±3°.	, (		או ולוכ	TM .	Micror	_
TOM-1545L-R.idw			a projects unlimited co	mc	Microp	J

TOM-1545L-R			
M: augusta augus	Edition	Sheet	
Microphone	-	1/1	

Date

1/24/2006 10/26/2010

Drawn Date

Approved by