

# U74LVC1G125

CMOS IC

## BUS BUFFER/LINE DRIVER 3-STATE


### ■ DESCRIPTION

The U74LVC1G125 is a single bus buffer/line driver with 3-state output. When the output enable ( $\overline{OE}$ ) is high the output will be disabled. In contrast, when the  $\overline{OE}$  is low, true data will pass from A input to the Y output.

This device has power-down protective circuit to prevent the device from destruction when it is powered down.

### ■ FEATURES

- \* Operate From 1.65V to 5.5V
- \* Inputs Accept Voltages to 5.5V
- \* High Noise Immunity
- \* Low Power Dissipation
- \* Direct Interface With TTL Level




### ■ ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen Free		
U74LVC1G125L-AE5-R	U74LVC1G125G-AE5-R	SOT-23-5	Tape Reel
U74LVC1G125L-AF5-R	U74LVC1G125G-AF5-R	SOT-25	Tape Reel
U74LVC1G125L-AL5-R	U74LVC1G125G-AL5-R	SOT-353	Tape Reel

U74LVC1G125L-AL5-R	(1) Packing Type (2) Package Type (3) Lead Free	(1) R: Tape Reel (2) AE5: SOT-23-5, AL5: SOT-353, AF5: SOT-25 (3) G: Halogen Free, L: Lead Free
--------------------	---	---

### ■ MARKING



## ■ PIN CONFIGURATION




## ■ FUNCTION TABLE


INPUT( $\overline{OE}$ )	INPUT(A)	OUTPUT(Y)
L	L	L
L	H	H
H	X	Z

Note: H: HIGH voltage level; L: LOW voltage level; X=don't care; Z=high-impedance OFF-state.

## ■ LOGIC DIAGRAM (Positive Logic)



Logic Symbol



IEC Logic Symbol

**■ ABSOLUTE MAXIMUM RATING**

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V <sub>CC</sub>	-0.5 ~ +6.5	V
Input Voltage	V <sub>IN</sub>	-0.5 ~ +6.5	V
Output Voltage	Enable mode	-0.5 ~ V <sub>CC</sub> + 0.5	V
	Disable mode		V
	Power-down mode		V
V <sub>CC</sub> or GND Current	I <sub>CC</sub>	±100	mA
Continuous Output Current (V <sub>OUT</sub> =0 to V <sub>CC</sub> )	I <sub>OUT</sub>	±50	mA
Input Clamp Current (V <sub>IN</sub> <0)	I <sub>IK</sub>	-50	mA
Output Clamp Current (V <sub>OUT</sub> >V <sub>CC</sub> or V <sub>OUT</sub> <0)	I <sub>OK</sub>	±50	mA
Power Dissipation (T <sub>A</sub> =-40°C ~ +125°C)	SOT-23-5	300	mW
	SOT-25		
	SOT-353		
Operating Temperature	T <sub>OPR</sub>	-40 ~ +125	°C
Storage Temperature	T <sub>STG</sub>	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

**■ RECOMMENDED OPERATING CONDITIONS**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V <sub>CC</sub>	Operating	1.65		5.5	V
Input Voltage	V <sub>IN</sub>		0		5.5	V
Output Voltage	V <sub>OUT</sub>	V <sub>CC</sub> =1.65V ~ 5.5V; Enable mode	0		V <sub>CC</sub>	V
		V <sub>CC</sub> =1.65V ~ 5.5V; Disable mode	0		5.5	V
		V <sub>CC</sub> =0V; Power-down mode	0		5.5	V
Input Transition Rise or Fall Rate	t <sub>R</sub> /t <sub>F</sub>	V <sub>CC</sub> =1.65V ~ 2.7V			20	ns/V
		V <sub>CC</sub> =2.7V ~ 5.5V			10	ns/V


■ ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ C$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
High-Level Input Voltage	$V_{IH}$	$V_{CC}=1.65V \sim 1.95V$		0.65* $V_{CC}$			V
		$V_{CC}=2.3V \sim 2.7V$		1.7			V
		$V_{CC}=2.7V \sim 3.6V$		2			V
		$V_{CC}=4.5V \sim 5.5V$		0.7* $V_{CC}$			V
Low-Level Input Voltage	$V_{IL}$	$V_{CC}=1.65V \sim 1.95V$			0.35* $V_{CC}$		V
		$V_{CC}=2.3V \sim 2.7V$			0.7		V
		$V_{CC}=2.7V \sim 3.6V$			0.8		V
		$V_{CC}=4.5V \sim 5.5V$			0.3* $V_{CC}$		V
High-Level Output Voltage	$V_{OH}$	$I_{OH}=-100\mu A$	$V_{CC}=1.65 \sim 5.5V$	$V_{CC}-0.1$			V
		$I_{OH}=-4mA$	$V_{CC}=1.65V$	1.2			V
		$I_{OH}=-8mA$	$V_{CC}=2.3V$	1.9			V
		$I_{OH}=-12mA$	$V_{CC}=2.7V$	2.2			V
		$I_{OH}=-24mA$	$V_{CC}=3.0V$	2.3			V
		$I_{OH}=-32mA$	$V_{CC}=4.5V$	3.8			V
Low-Level Output Voltage	$V_{OL}$	$I_{OL}=100\mu A$	$V_{CC}=1.65 \sim 5.5V$			0.1	V
		$I_{OL}=4mA$	$V_{CC}=1.65V$			0.45	V
		$I_{OL}=8mA$	$V_{CC}=2.3V$			0.3	V
		$I_{OL}=12mA$	$V_{CC}=2.7V$			0.4	V
		$I_{OL}=24mA$	$V_{CC}=3.0V$			0.55	V
		$I_{OL}=32mA$	$V_{CC}=4.5V$			0.55	V
Input Leakage Current	$I_{I(LEAK)}$	$V_{IN}=5.5V$ or GND, $V_{CC}=5.5V$			$\pm 0.1$	$\pm 5$	$\mu A$
Power OFF Leakage Current	$I_{OFF}$	$V_{IN}$ or $V_{OUT}=5.5V$ , $V_{CC}=0V$			$\pm 0.1$	$\pm 10$	$\mu A$
3-State Output OFF-State Current	$I_{OZ}$	$V_{IN}=V_{IH}$ or $V_{IL}$ , $V_{OUT}=V_{CC}$ or GND, $V_{CC}=5.5V$			$\pm 0.1$	$\pm 10$	$\mu A$
Quiescent Supply Current	$I_Q$	$V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$ , $V_{CC}=5.5V$			0.1	10	$\mu A$
Additional Quiescent Supply Current Per Input Pin	$\Delta I_Q$	$V_{CC}=2.3 \sim 5.5V$ , $V_{IN}=V_{CC}-0.6V$ , $I_{OUT}=0$			5	500	$\mu A$

■ SWITCHING CHARACTERISTICS ( $T_A=25^\circ C$ )



PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Propagation Delay From Input A to Output Y	$t_{PLH} / t_{PHL}$	$V_{CC}=1.8 \pm 0.15V$ , $R_L=1K\Omega$	$C_L=30pF$	1.0	3.3	8.0	ns
		$V_{CC}=2.5 \pm 0.2V$ , $R_L=500\Omega$		0.5	2.2	5.5	ns
		$V_{CC}=2.7V$	$C_L=50pF$ , $R_L=500\Omega$	0.5	2.5	5.5	ns
		$V_{CC}=3.3 \pm 0.3V$		0.5	2.1	4.5	ns
		$V_{CC}=5 \pm 0.5V$		0.5	1.7	4.0	ns
3-State Output Enable Time From Input $\overline{OE}$ to Output Y	$t_{PZH} / t_{PZL}$	$V_{CC}=1.8 \pm 0.15V$ , $R_L=1K\Omega$	$C_L=30pF$	1.0	4.1	9.4	ns
		$V_{CC}=2.5 \pm 0.2V$ , $R_L=500\Omega$		0.5	2.8	6.6	ns
		$V_{CC}=2.7V$	$C_L=50pF$ , $R_L=500\Omega$	0.5	3.3	6.6	ns
		$V_{CC}=3.3 \pm 0.3V$		0.5	2.4	5.3	ns
		$V_{CC}=5 \pm 0.5V$		0.5	2.1	5.0	ns
3-State Output Disable Time From Input $\overline{OE}$ to Output Y	$t_{PLZ} / t_{PHZ}$	$V_{CC}=1.8 \pm 0.15V$ , $R_L=1K\Omega$	$C_L=30pF$	1.0	4.3	9.2	ns
		$V_{CC}=2.5 \pm 0.2V$ , $R_L=500\Omega$		0.5	2.7	5.0	ns
		$V_{CC}=2.7V$	$C_L=50pF$ , $R_L=500\Omega$	0.5	3.0	5.0	ns
		$V_{CC}=3.3 \pm 0.3V$		0.5	3.1	5.0	ns
		$V_{CC}=5 \pm 0.5V$		0.5	2.2	4.2	ns

## ■ TEST CIRCUIT AND WAVEFORMS



TEST CIRCUIT

$V_{CC}$	INPUTS		$V_M$	$V_{LOAD}$	$V_\Delta$	$C_L$	$R_L$
	$V_{IN}$	$t_R, t_F$					
$1.8V \pm 0.15V$	$V_{CC}$	$\leq 2ns$	$V_{CC}/2$	$2 \times V_{CC}$	0.15V	30pF	$1K\Omega$
$2.5V \pm 0.2V$	$V_{CC}$	$\leq 2ns$	$V_{CC}/2$	$2 \times V_{CC}$	0.15V	30pF	$500\Omega$
2.7V	2.7V	$\leq 2.5ns$	1.5V	6V	0.3V	50pF	$500\Omega$
$3.3V \pm 0.3V$	2.7V	$\leq 2.5ns$	1.5V	6V	0.3V	50pF	$500\Omega$
$5V \pm 0.5V$	$V_{CC}$	$\leq 2.5ns$	$V_{CC}/2$	$2 \times V_{CC}$	0.3V	50pF	$500\Omega$



Note:  $C_L$  includes probe and jig capacitance.

All input pulses are supplied by generators having the following characteristics:  $P_{RR} \leq 10MHz$ ,  $Z_0 = 50\Omega$ .

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.