

## Silicon Power Schottky Diode

$V_{RRM} = 45\text{ V}$


$I_F = 60\text{ A}$

### Features

- High Surge Capability
- Types up to 45 V  $V_{RRM}$

### Note:

1. Standard polarity: Stud is cathode.
2. Reverse polarity (R): Stud is anode.
3. Stud is base.



DO-5 Package



### Maximum ratings, at $T_j = 25\text{ °C}$ , unless otherwise specified ("R" devices have leads reversed)

Parameter	Symbol	Conditions	SD51 (R)	Unit
Repetitive peak reverse voltage	$V_{RRM}$		45	V
RMS reverse voltage	$V_{RMS}$		32	V
DC blocking voltage	$V_{DC}$		45	V
Continuous forward current	$I_F$	$T_C \leq 100\text{ °C}$	60	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25\text{ °C}$ , $t_p = 8.3\text{ ms}$	800	A
Operating temperature	$T_j$		-65 to 150	°C
Storage temperature	$T_{stg}$		-65 to 175	°C

### Electrical characteristics, at $T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Conditions	SD51 (R)	Unit
Diode forward voltage	$V_F$	$I_F = 60\text{ A}$ , $T_j = 25\text{ °C}$	0.66	V
Reverse current	$I_R$	$V_R = 45\text{ V}$ , $T_j = 25\text{ °C}$ $V_R = 45\text{ V}$ , $T_j = 125\text{ °C}$	5 200	mA

### Thermal characteristics

Parameter	Symbol	Conditions	SD51 (R)	Unit
Thermal resistance, junction - case	$R_{thJC}$		1.0	°C/W





Figure 4  
Typical Reverse Characteristics

