

## PEEK

## Secures performance of sensitive items in challenging environments

Similar to PPS, but with a substantially expanded operating temperature range, PEEK (PolyEtherEther-Ketone) is a high performance advanced polymer with outstanding physical properties. PEEK is inherently flame retardant, with a V-0 flammability rating, will withstand continuous use in superheated water or steam up to 500°F, and resists most acids, solvents and bases.

PEEK is FDA approved as a food contact product, resists damage from radiation and will continue to perform in UHV (Ultra High Vacuum) environments. PEEK is extensively used in the aerospace, automotive, teletronic and chemical process industries, and is considered an advanced biomaterial used in medical implants and other biomedical applications. PEEK will withstand thousands of sterilization cycles without damage or degradation.

Flexo PEEK expandable sleeving is tightly braided from 10 mil filaments of pure, unfilled PEEK polymer. The sleeving expands to fit over connectors and splices, and provides a full coverage over wires hoses and cable bundles in advanced engineering applications.



Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		Available	Lbs/
		Min.	Max.	Bulk Spool	Shop Spool	Colors	100'
1/8″	PKN0.13BK	1/16″	5/16″	1,000′	225′	Black (BK)	0.16
1/4″	PKN0.25BK	7/64″	9/16″	1,000′	200′	Black (BK)	0.19
3/8″	PKN0.38BK	5/32″	5/8″	500′	125′	Black (BK)	0.31
1/2″	PKN0.50BK	3/16″	15/16″	500′	100′	Black (BK)	0.44
5/8″	PKN0.63BK	1/4″	1 1/4″	500′	100′	Black (BK)	0.51
3/4″	PKN0.75BK	3/8″	1 3/8″	250′	75′	Black (BK)	0.64
1″	PKN1.00BK			250′	65′	Black (BK)	0.71
1 1/4″	PKN1.25BK			250′	50′	Black (BK)	0.86
1 1/2″	PKN1.50BK			200′	40′	Black (BK)	1.28
1 3/4″	PKN1.75BK			200′	30′	Black (BK)	1.61
2″	PKN2.00BK			200′	50′	Black (BK)	2.14

1

A PEEK<sup>®</sup> is a registered trademark of the Victrex Corporation.

- High Chemical & Insoluble Resistance in Common Solvents Including Acids, Salts and Oil
- Very Light Weight
- Excellent Strength in High Temperature & Harsh Environments
- Low Outgassing
- V-O Flammability Rating
- Halogen Free
- Non-Corrosive and Non-Conductive







