


**CF**  
**Unsplit Nylon Conduit**

- Wire and cable protection for electrical harnesses
- Can be used to protect hydraulic hoses
- Temperature range: -40°F - 300°F (-40°C - 149°C)
- Flexible body allows for corner/elbow wiring



Material: UL94 HB Nylon Color: Black with Grey Stripe							
Part No	Nominal Ø	"A" Min	"A" Max	"B" Min	"B" Max	Wall Thickness	Standard Pack
CF1010A	1/4 (6.4)	.237 (6)	.266 (6.8)	.375 (9.5)	.400 (10.2)	.004 (.1)	2,500 Ft (762m)
CF1020A	3/8 (9.5)	.341 (8.7)	.380 (9.7)	.497 (12.6)	.526 (13.4)	.004 (.1)	1,500 Ft (457.2m)
CF1040A	7/16 (11.1)	.399 (10.1)	.437 (11.1)	.573 (14.6)	.597 (15.2)	.005 (.1)	1,500 Ft (457.2m)
CF1060A	1/2 (12.7)	.473 (12)	.516 (13.1)	.664 (16.9)	.700 (17.8)	.005 (.1)	1,000 Ft (304.8m)
CF1080A	5/8 (15.9)	.603 (15.3)	.639 (16.2)	.805 (20.5)	.837 (21.3)	.005 (.1)	700 Ft (213.4m)
CF1090A	3/4 (19.1)	.707 (18)	.759 (19.3)	.950 (24.1)	.989 (25.1)	.005 (.1)	450 Ft (137.2m)
CF1140A	1 (25.4)	1.020 (25.9)	1.069 (27.2)	1.251 (31.8)	1.304 (33.1)	.006 (.2)	250 Ft (76.2m)
CF1150A	1-1/8 (28.6)	1.122 (28.5)	1.176 (29.9)	1.356 (34.6)	1.413 (35.9)	.006 (.2)	200 Ft (60.9m)