


PART NO.	DIM. "A" ±.015(0.4)
CRLCBSR-3-01	3/16 (4.8)
CRLCBSR-4-01	1/4 (6.4)
CRLCBSR-5-01	5/16 (8.0)
CRLCBSR-6-01	3/8 (9.5)
CRLCBSR-8-01	1/2 (12.7)
CRLCBSR-12-01	3/4 (19.0)

TO SNAP-LOCK IN A .157±.003 (4.0±0.08) DIA. HOLE, IN A .063 (1.6) NOMINAL THICK BOARD

TO SNAP-LOCK IN A .236±.003 (6.0±0.08) DIA. HOLE, IN A

.031-.047 (0.8-1.2) PANEL THICKNESS



NOTES:

1. MATERIAL: NYLON 6/6 (RMS-01).
FLAME RETARDANT, NYLON (RMS-19),
AVAILABLE BY SPECIAL ORDER ONLY.
TO ORDER, REPLACE "-01" WITH "-19"

2. MATERIAL: NYLON 4/6, HEAT STABILIZED, (RMS-109) AVAILABLE BY SPECIAL ORDER ONLY. TO ORDER, REPLACE "-01" WITH "-109".

3. COLOR: NATURAL.
BLACK, AVAILABLE BY SPECIAL ORDER ONLY.
TO ORDER, ADD "BK" TO PART NO.

F E		SM 06.06.02 SM 05.08.02 PB 07.10.95		JPPED	REVERSE LOCKIN	G CBS, ROUND HOLE	DWG IN IN (MM)
C	DIM. TO S-L IN .24 (6.0) ADDED; TABLE REDUCED; UL NOTES ADDED  DIMS IN CHASSIS THKNS PUT TO 3 PLACES CONVERTED TO ACAD; DIM "A" WAS .411	PB 11.23.94 PB 07.29.94	TOLERANCES		CRLCBSR SEE NOTES	DWN: P.B. APP: DT: 07-29-94 DT:	FINAL PART # PRIN
Ā	COMLETE REDRAW, .40 WAS .39, .06 WAS .07, RMS-01 WAS RMS-48	RT 03.10.94  ENGR DATE	.XXX=±.005 FRAC=1/64 ANG=1*	RE:	RICHCO, INC.	RICHCO INC. PO BOX 804238,CHICAGO,60680 (773) 539-4060	SEE TABLE CA

.39 (10.0)