



AC-DC UL/cUL ADAPTOR DC 4.5V 250mA

REV. Status

REVISION -	10/24/01	RJ
REVISION A	CHANGED A.6	05/14/02 RJ
REVISION B	REVISED PLUG LOCATION. ADDED RoHS	05/17/06 MP
REVISION C	WITHSTAND VOLTAGE WAS 1500Vrms	08/01/06 MP

A. Electrical specifications

- Input voltage: AC 120V ±10% 60Hz ±0.5Hz
- Output voltage and current: DC 4.5V at 250mA

V_{in}	100% Load	No Load
108	2.8VDC MIN	-
120	4.0-5.0VDC	8.5VDC MAX
132	-	9.5VDC MAX

NOTE: Specification applies after 10 minutes warm-up with full load and at any operating temperature.


- Operating temperature: -10 °C to +40 °C
- Storage temperature: -20 °C to +85 °C
- Operating and Storage Humidity: 0 to 95% without condensation
- Withstand voltage: 1000Vrms 1 minute @ input to output

B. Typical performance data test Condition:
 Ta= +25°C measured after 10 minute warm-up with input at 120V 60Hz


C. Safety agencies

UL and cUL File No. E218172

D. Nameplate: Information is as follows:
 Metallic letters on a black background




TYPICAL PERFORMANCE CHART



E. Mechanical Specifications

All dimensions shown are nominal unless otherwise specified



PREPARED BY:

K. BRENNAN

ENGINEER:

M. PITCHAI

QUALITY CONTROL:

T. CLEM

APPROVED:

Y. SEKIGUCHI

DWG CONTROL NO. P-A7-12921
 ACAD\PS\129211.DWG

REV C

UL/cUL DC 4.5V 250mA
 POWER SUPPLY

TAMURA CORPORATION OF AMERICA
 43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
 (951) 699-1270 FAX 9516769482

212AS04025

MODEL SPECIFICATION

DIM: mm(In) SCL: NONE SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.