



LINEAR WALL PLUG ADAPTOR 9VDC 125mA



REV. Status

REVISION -  
10/25/01 RJ

REVISION A  
UPDATED RIPPLE  
VOLTAGE  
02/06/02 RJ

REVISION B  
CHANGED A.6  
05/14/02 RJ

REVISION C  
REVISED PLUG  
LOCATION. ADDED  
RoHS  
05/17/06 MP

REVISION D  
WITHSTAND  
VOLTAGE WAS  
1500Vrms  
08/01/06 MP

REVISION E  
ADDED NOTE 7.  
UPDATED LABEL  
AND SAFETY.  
FORMAT ERROR  
06/21/07 MP

A. Electrical specifications

- Rated Input voltage: AC 120V 60Hz
- Output voltage and current: DC 9V at 125mA

V <sub>in</sub>	100% Load	No Load
108	7.0VDC MIN	-
120	8.5-9.5VDC	14.5VDC MAX
132	-	16.0VDC MAX


NOTE: Specification applies after 10 minutes warm-up with full load and at any operating temperature.

- Operating temperature: -10 °C to +30 °C
- Storage temperature: -20 °C to +85 °C
- Operating and Storage Humidity: 0 to 95% without condensation
- Withstand voltage: 1240Vrms @ input to output
- Does not meet CEC (California Energy Commission) regulations.


B. Typical performance data test Condition:  
Ta = +25°C measured after 10 minute warm-up with input at 120V 60Hz

C. Safety:  
Certified to UL1310 and CSA No. 223  
File No. E218172

D. Nameplate: Information is as follows:  
Metallic letters on a black background




TYPICAL PERFORMANCE CHART



E. Mechanical Specifications

All dimensions shown are nominal unless otherwise specified



PREPARED BY:

K. BRENNAN

ENGINEER:

M. PITCHAI

SAFETY ENGINEER:

B. OCONNELL

APPROVED:

Y. SEKIGUCHI

DWG CONTROL NO.  
P-A7-12923  
ACAD\PS\A7129231.DWG

REV  
E

9VDC 125mA  
LINEAR WALL PLUG ADAPTOR

**TAMURA CORPORATION OF AMERICA**  
43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624  
(951) 699-1270 FAX 9516769482

212AS09012

MODEL SPECIFICATION

DIM: mm [In] | SCL: NONE | SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.