

30-00006


Wire, 3C, 24 AWG, 300V, 80C, 3.4 mm, PVC,

65P

date: August 13, 2012

rev: Α1 page: 1 of 2

Wire cross section:



Cable specifications:

conductors

gauge (AWG)	24
material	bare copper
cord size (strands)	11 x 0.16

jacket

material	80°C, 65P, PVC
color	black
diameter (mm)	3.4

insulation

material	35P, PVC
color	red, black, green
diameter (mm)	1.1 ± 0.05

electrical properties

rated voltage (V)	300
rated temperature (°C)	80
operating temperature (°C)	-5 ~ +80
resistance at 20° C (Ohm/Km) max	87.5
spark test (Kv)	2.5/3.0

physical characteristics

material		insulation/jacket PVC
unaged	tensile strength (kgf/mm² min)	1.05
	elongation (% min)	100
aging test	condition	100 °C/168 h
	elongation (% unaged min)	65
	tensile strength (% unaged min)	70
deformation (121± 1 °C x 1 hour)		≤50%

tolerance X: ±0.5 mm .X: ±0.3 mm .XX: ±0.05 mm applicable unless otherwise indicated in specification or on drawings

Initial Date



30-00006

Wire, 3C, 24 AWG, 300V, 80C, 3.4 mm, PVC, 65P

date: August 13, 2012 rev: Α1 page: 2 of 2

Revision notes:

Rev	Date	Description
Α	March 14, 2011	initial release
A1	August 13, 2012	added operating temperature

-				
⋖	20CIT	ication	ıΔn	nroval
9	56 611	Lation	np	piovai

Spec sign-off verifies that you have reviewed the entire specification, tested a sample of the product, and confirm that it meets your requirements. This specification reflects the part as it will be ordered. Orders will not be processed until the specification pages have been initialed and the approval page has been signed. This specification is confidential and is not to be transmitted without prior approval from Tensility.

Signature	Title ————
Name	Date
Company	Branch