


0.020" ± 0.002" DIAMETER,  
24 AWG, TINNED CCS,  
1.0" LONG MINIMUM



RESISTANCE @ +25°C = 50,000 Ω ± 5%  
RESISTANCE/TEMPERATURE CURVE = "J"  
BETA "β" (0 TO +50°C) = 3,892°K NOMINAL  
TEMPERATURE COEFFICIENT @ +25°C = -4.4%/°C NOMINAL  
DISSIPATION CONSTANT = 2 mW/°C NOMINAL (STILL AIR)  
THERMAL TIME CONSTANT = 5 SECONDS NOMINAL (STILL AIR)  
THERMAL TIME CONSTANT = 0.5 SECONDS NOMINAL (STIRRED OIL)  
MAXIMUM TEMPERATURE RATING = +300°C

---	ISO RELEASE	02/23/04	DD
"A"	LEAD WIRE DIAMETER WAS 0.020" ± 0.001"	02/23/04	DD
REV	REVISION RECORD	DATE	APP

SCALE	NONE	<b>U.S. SENSOR</b> CORP. 1832 W. COLLINS AVE. ORANGE, CA. 92867 714-639-1000 www.ussensor.com
DRAWN BY	DAN DANKERT	
DATE	03/18/92	
REV.	"A"	
LAYER	0 OF 1	<b>NTC THERMISTOR</b> P/N 503JG1J