



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SMX1200XLHG

### SmartPro Medical Grade 1kVA 230V Line interactive Tower UPS, Extended-run, full isolation, USB and Serial ports



#### Highlights

- 1000VA / 1kVA line interactive, extended run tower UPS
- Maintains 230V nominal output over an input range of 155 to 274V
- Professional features include serial port, IEC320 plug & outlets, built-in isolation transformer
- Input: IEC C14 inlet (230V 5A) / Output: 6 IEC C13 (230V)

#### Description

Tripp Lite's SMX1200XLHG offers medical-grade UPS protection with built-in line-interactive voltage regulation, expandable battery runtime and intelligent monitoring with unattended shutdown capability. Tested to CE/IEC 60601-1 standard as medical electrical equipment. Built-in isolation transformer with Faraday shield offers full line isolation and removes common mode noise while maintaining full AC surge suppression in all modes. Includes high quality hospital-grade plug and outlets. Resistant to electrostatic discharge. 1000VA power handling capacity supports computers, inter-networking equipment and other critical loads during commercial power failures. External battery connector allows configuration for up to several hours of runtime during power failures by adding one or more external battery packs (BP36V15-2U limit 1 or BP36V42-3U multi-pack compatible). Line interactive voltage regulation corrects brownouts as low as 155V and overvoltages as high as 274V back to normal 230V levels, saving battery reserves for use only during complete power failures. Includes diagnostic LEDs and 2 built-in communications ports (1 USB, 1 DB9) that work with included PowerAlert Software and cabling to provide automatic unattended shutdown of connected network and PC applications.

#### Applications

CE/IEC 60601-1 compliant UPS provides ultimate safety and reliability for patient point of care solutions, telemedicine, nurse's stations, wireless communications systems, electronic prescribing applications, medical imaging and mission critical equipment. Not recommended for life support applications

#### Package Includes

- SMX1200XLHG Medical Grade Tower UPS System
- PowerAlert Software and cabling
- Warranty information
- Instruction manual

#### Features

- Ideal UPS protection for applications in medical patient-care areas where CE/IEC 60601-1 listed medical electrical equipment is required
- Built-in isolation transformer with Faraday shield offers full isolation and removes common mode noise while maintaining full AC surge suppression in all modes
- Provides connected equipment with continuous power during short and long duration loss of commercial power
- Expandable runtime is available with the addition of one or more external battery packs (BP36V15-2U limit 1 or BP36V42-3U multi-pack)

compatible)

- Line-interactive voltage regulation corrects brownouts and overvoltages from 155 to 274 volts back to usable 230V output levels, without using battery power
- Full line isolation prevents shock potential and operational problems in sensitive electronic equipment
- Resistant to electrostatic discharge
- Supports loads up to 1000VA/750W
- 27.5 min. half-load runtime (500VA/375W), 11 min. full load runtime (1000VA/750W)
- 6 protected outlets; 6-inch dangle with IEC C14 inlet
- USB and DB9 communication ports
- PowerAlert unattended shutdown software and complete cabling included
- Complete surge protection, line isolation and EMI/RFI noise filtering
- 5 diagnostic LEDs indicate AC present, on battery, voltage correction, overload & battery low/replace
- Battery replacement door and back panel grounding lug

## Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	1000
Output Watt Capacity (watts)	750
Nominal Output Voltage(s) Supported	220V; 230V; 240V
Nominal Voltage details	230v nominal inverter output voltage
Frequency compatibility	50/60 Hz (auto-selectable)
Output voltage regulation (line mode)	-18%, +8%
Built-in UPS output receptacles	6 C13 outlet(s)
INPUT	
Rated input current (at maximum load)	5A
Nominal Input Voltage(s) Supported	230V AC
UPS input connection type	C14 inlet
UPS Input cord length (ft.)	6 inch dangle, 16 gauge
UPS Input cord length (m)	1.83
Recommended Electrical Service	10A 230V
Voltage compatibility (VAC)	230
BATTERY	
Full load runtime (minutes)	11 min. (750w)
Half load runtime (minutes)	27.5 min. (375w)

<b>Expandable battery runtime</b>	Supports extended runtime with optional <a href="#">BP36V15-2U</a> (limit 1) and <a href="#">BP36V42-3U</a> external battery pack (multi-pack compatible)
<b>External battery pack compatibility</b>	<a href="#">BP36V15-2U</a> (limit 1); <a href="#">BP36V42-3U</a> (multi-pack compatible)
<b>DC system voltage (VDC)</b>	36
<b>Battery recharge rate (included batteries)</b>	Less than 4.5 hours from 10% to 90%
<b>Replacement battery cartridge (internal UPS battery replacement)</b>	<a href="#">RBC53</a>
<b>Battery Access</b>	Battery access door allows hot swap battery replacement without powering connected equipment off
<b>Typical battery lifespan</b>	3-6 years, depending on usage
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description</b>	Line interactive UPS offers 2 boost levels of brownout correction and a single level of overvoltage adjustment to maintain usable, computer grade output without consuming battery power over an input voltage range of 155 to 274V AC.
<b>Overvoltage correction</b>	Input voltages between 245 and 274V AC are reduced by 9%
<b>Undervoltage correction</b>	Input voltages between 183 and 199 are boosted by 10%
<b>Severe undervoltage correction</b>	Input voltages between 156 and 182 are boosted by 21%
<b>Direct pass through</b>	Input voltages between 200 and 244V AC are passed through unchanged
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>LED Indicators</b>	5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status
<b>Alarms</b>	3 function audible alarm indicates power failure conditions (4 short beeps every 10 seconds), overload (continuous short beeps) and low battery (continuous tone)
<b>Switches</b>	Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions
<b>SURGE / NOISE SUPPRESSION</b>	
<b>UPS AC suppression joule rating</b>	340 joules
<b>EMI / RFI AC noise suppression</b>	Yes
<b>AC suppression response time</b>	Instantaneous
<b>PHYSICAL</b>	
<b>Installation form factors supported with included accessories</b>	Tower
<b>Installation form factors supported with optional accessories</b>	Wallmount (UPSWM - tower mounting kit)
<b>UPS / Power Module dimensions in primary form factor (height x width x depth / inches)</b>	12.7 x 7.5 x 9.1

UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	32.3 x 19 x 23.1
UPS / Power Module weight (lbs)	45.5
UPS / Power Module weight (kg)	20.7
UPS Shipping dimensions (height x width x depth / inches)	18.5 x 12.2 x 13.4
UPS Shipping dimensions (height x width x depth / cm)	47 x 31 x 34
Shipping weight (lbs)	48.8
Shipping weight (kg)	22
Cooling method	UPS cooling via rear-exit fan
UPS housing material	PVC
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	252.2
Battery mode BTU / hr. (full load)	252.2
<b>COMMUNICATIONS</b>	
Communications interface	USB; DB9 Serial
Software and cabling included	PowerAlert UPS monitoring software is included on CD-ROM for all common network and standalone operating systems. Ships with 2 cables, 1-USB to USB & 1-DB9 to DB9
<b>LINE / BATTERY TRANSFER</b>	
Transfer time	2-4 milliseconds
Low voltage transfer to battery power (setpoint)	155
High voltage transfer to battery power (setpoint)	274
<b>SPECIAL FEATURES</b>	
Grounding lug	Back panel grounding lug
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
Appearance	Attractive gray tower UPS

**CERTIFICATIONS**

<b>Certifications</b>	Tested to CE, IEC 60601-1 (Medical), Class B (Emissions)
-----------------------	--

**WARRANTY**

<b>Product Warranty Period (International)</b>	2-year limited warranty
--	-------------------------

<b>Product Warranty Period (Mexico)</b>	2-year limited warranty
---	-------------------------

<b>Product Warranty Period (Puerto Rico)</b>	2-year limited warranty
--	-------------------------

**Related Items****Optional Products**

<b>Related Model</b>	<b>Description</b>	<b>Qty.</b>
<a href="#">BP36V15-2U</a>	BP36V15-2U - External Battery Pack for UPS System	1
<a href="#">BP36V42-3U</a>	BP36V42-3U - External Battery Pack for UPS System	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3868](http://www.tripplite.com/en/products/model.cfm?txtModelID=3868).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.