



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SU30K3/3XR5

SmartOnline 30kVA On-Line Double-Conversion UPS, 3 Phase input / output with oversize battery set



Highlights

- 30,000 VA (30kVA) EXTENDED RUNTIME tower UPS with internal batteries
- Saves valuable space and simplifies runtime scalability
- 3-phase hardwire input and output (120/208VAC). Wide input voltage correction range (96 - 144V AC / 166 - 250V AC)
- IGBT technology and zero transfer time, on-line, double-conversion operation
- 3 communication ports, SNMP card slot and EPO jack

Description

Tripp Lite's SU30K3/3XR5 30kVA SmartOnline 3-Phase Intelligent, True On-Line Extended Runtime UPS System has been redesigned to save valuable space and simplify runtime scalability. Power and battery components are combined into a single, small-footprint module (the smallest in its class). A robust internal battery runtime capability can be easily extended by installing additional optional internal battery packs through the convenient front panel access door. The SU30K3/3XR5 features a large internal battery compartment that contains more internal batteries than the equivalent standard-run model (SU30K3/3) and more space to add additional optional internal battery packs to extend runtime. The SU30K3/3XR5 provides mission critical equipment with the highest level of power protection available. Large capacity 30,000VA/24,000 watt UPS continually converts incoming AC power into filtered DC power, and then resynthesizes it back into AC power with a pure sine wave. Perfectly regulated, continuous sine wave output with zero transfer time offers compatibility with all equipment types. IGBT inverter technology produces output power with <3% THD (total harmonic distortion), allowing connected equipment to perform at its peak. A 3:1 crest factor safely supports a variety of equipment, even those with wildly-fluctuating power demands. Extremely efficient operation saves money by lowering electricity consumption. Hardwire input and output connections support a variety of permanent or PDU style power connections. SU30K3/3XR5 features 120/208V AC, 3-phase, 4-wire (plus ground), wye input and output. It also features a wide input voltage correction range: 96 -144/166-250V AC. Frequency is 50 or 60 Hz (auto-selectable). SU30K3/3XR5 includes internal power and battery components in a single small-footprint tower module. Battery support can be extended with additional internal battery packs. A manual bypass switch as well as an automatic bypass function ensure 100% availability of connected equipment by safely passing through AC power when the UPS requires maintenance. Three built-in communication ports (RS-232, contact closure and AS-400) work with included PowerAlert Software to simultaneously provide shutdown commands and reporting on multiple servers without the need for costly accessories. An accessory slot accepts an optional internal SNMP card (model # SNMPWEBCARD) for remote shutdowns, reboots and more. A Battery Start Switch allows cold restart of UPS during a prolonged blackout to utilize its batteries for periodic system access or data retrieval. An Emergency Power Off button turns UPS output OFF and disables Bypass output. Built-in Emergency Power Off (EPO) interface supports remote emergency shutdown in large facilities. Front panel combination LCD/LED display alerts users to a variety of UPS operational modes and conditions. A start-up service program is recommended to enhance the reliability of the installation.

Package Includes

- SU30K3/3XR5 UPS System (power and battery components in one module)
- PowerAlert Software and cabling
- Warranty information
- Instruction manual

Features

- Large internal battery compartment contains more internal batteries than the equivalent standard-run model (SU30K3/3) and more space to add additional optional internal battery packs to extend runtime. Saves valuable space: power and battery components combined into a single small-footprint module
- Simplifies runtime scalability: convenient front panel battery access for expandable runtime with additional internal battery packs
- True on-line, double conversion UPS with IGBT technology provides pure, sine wave AC output at all times
- Maintains continuous operation through blackouts, voltage fluctuations and surges with zero transfer time
- Removes harmonic distortion, electrical impulses, frequency variations and other hard-to-solve power problems
- 30,000VA/24,000 watt power capacity with 3-phase, hardwire 120/208V AC input/output connections
- Features a wide input voltage correction range: 96 - 144/166 - 250V AC

- 61 minutes runtime at half load (11,300 watts) based on adding 3 SURBC2030 battery packs and 11 minutes runtime at full load (24,000 watts)
- 3:1 crest factor safely supports a variety of equipment, even those with wildly-fluctuating power demands
- Extend runtime by installing optional internal battery packs (model # SURBC2030) through the front panel access door. SU30K3/3XR5 includes 5 internal battery packs and accepts 3 additional internal battery packs. A standalone battery module compartment with a 4 battery pack capacity and daisy-chain capability (model # SUBF2030) is available to further extend runtime.
- 3 communication ports (RS-232, contact closure and AS-400)
- Slot for optional SNMP card (model # SNMPWEBCARD)
- Manual bypass switch as well as an automatic bypass function ensures 100% availability of connected equipment by safely passing through AC power when the UPS system requires maintenance
- Battery Start Switch allows cold restart of UPS during a prolonged blackout to utilize its batteries for periodic system access or data retrieval
- Emergency Power Off button turns UPS output OFF and disables Bypass output
- PowerAlert Universal UPS Power Management Software and 6 ft. communication cable included
- Built-in Emergency Power Off (EPO) interface supports remote emergency shutdown in large facilities
- Combination LED/LCD display
- Start-up service program is recommended to enhance the reliability of the installation

Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	30000
Output kVA capacity (kVA)	30
Output Watt Capacity (watts)	24000
Output kW capacity	24
Output power factor	0.8
Crest Factor	3:1
Nominal Output Voltage(s) Supported	120/208V; 3-Phase Wye
Frequency compatibility	50 / 60 Hz
Output voltage regulation (line mode)	+/- 2%
Output voltage regulation (Battery mode)	+/- 2%
Built-in UPS output receptacles	Hardwire
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	Pure Sine wave
INPUT	
Rated input current (at maximum load)	90A (per phase, online)

Nominal Input Voltage(s) Supported	120V / 208V 3 phase wye
UPS input connection type	Hardwire
UPS input connection description	120/208V (3-Phase, 4 Wire, wye)
Phase	3-Phase
BATTERY	
Full load runtime (minutes)	11 min. (24kw)
Half load runtime (minutes)	25 min. (12kw)
Expandable battery runtime	Supports extended runtime with optional external battery packs
External battery pack compatibility	SURBC2030 ; SUBF2030 (holds 4 SURBC2030)
Expandable runtime description	Includes a battery housing with space for 3 internal SURBC2030 battery packs for extended runtime. Additional runtime capacity is available by adding SUBF2030 and additional SURBC2030 batteries - see runtime chart for specific recommendations
DC system voltage (VDC)	240
Battery recharge rate (included batteries)	2 - 4 hours from 10% to 90%
Replacement battery cartridge (internal UPS battery replacement)	SURBC2030
Battery Access	Front panel internal battery access door
Battery replacement description	Hot-swappable, replaceable batteries
VOLTAGE REGULATION	
Voltage regulation description	Online, double-conversion power conditioning
Overvoltage correction	Maintains continuous operation without using battery power during overvoltages to 144 / 250 (3-Phase, 4-Wire, wye), reducing output within 2% of nominal
Undervoltage correction	Maintains continuous operation without using battery power during brownout / undervoltage conditions to 96 / 166 (3-Phase, 4-Wire, wye)
LEDS ALARMS & SWITCHES	
LED Indicators	7 LED DISPLAY: AC input, bypass input, AC-DC charger, DC-AC inverter, AC output, bypass operation and battery operation
Front panel LCD display	SELECTABLE LCD DISPLAY: indicates a wide range of UPS operational and fault/warning conditions including operational mode, alarm/shutdown conditions, input/output voltage/frequency, battery voltage, load percentage and more (see manual)
Alarms	Alarms warn against a variety of operational conditions: low-battery, overload, shutdown, bypass and more

Alarm cancel operation	Power-fail alarm can be silenced using alarm-cancel switch
Switches	"ON" button turns UPS's inverter ON. "OFF" button turns UPS's inverter OFF. "Select" Button browses through items displayed on LCD screen. "Enter" button selects items displayed on LCD screen. "Select" and "Enter" buttons used simultaneously mute UPS alarms. "Battery Start" Switch cold starts the inverter. "Emergency Power Off" button turns UPS output OFF and disables Bypass output. "Manual Bypass" switch bypasses the UPS's inverter during maintenance.
SURGE / NOISE SUPPRESSION	
UPS AC suppression joule rating	2032
UPS AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
AC suppression joule rating	2032
AC suppression response time	Instantaneous
PHYSICAL	
Installation form factors supported with included accessories	Tower
Primary form factor	Tower
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	50.9 x 19.5 x 36.8
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	129.3 x 49.5 x 93.5
Installed whole system maximum rack depth (cm)	0
UPS / Power Module weight (lbs)	935
UPS / Power Module weight (kg)	424.5
UPS Shipping dimensions (height x width x depth / inches)	61.5 x 31 x 44.5
UPS Shipping dimensions (height x width x depth / cm)	156.2 x 78.7 x 113
Shipping weight (lbs)	1152

Shipping weight (kg)	523
Cooling method	Fans
UPS housing material	Steel
ENVIRONMENTAL	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius.
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius.
Relative Humidity	0 to 95%, non-condensing
COMMUNICATIONS	
Communications interface	DB9 Serial; Contact closure; Slot for SNMP/Web interface
Network monitoring port description	RS232, contact closure and AS400 monitoring ports are supported by 3 separate DB9 ports
PowerAlert software	Included
Communications cable	DB9 cabling included
LINE / BATTERY TRANSFER	
Transfer time	No transfer time (0 ms.) in online, double-conversion mode
Low voltage transfer to battery power (setpoint)	Maintains continuous operation during undervoltages as low as 96 / 166V AC (3-Phase, 4-Wire, wye). Below this point, output is maintained utilizing battery reserves.
High voltage transfer to battery power (setpoint)	Maintains continuous operation during overvoltages as high as 144 / 250V AC (3-Phase, 4-Wire, wye). Above this point, output is maintained utilizing battery reserves.
SPECIAL FEATURES	
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
High availability UPS features	Automatic inverter bypass; Hot swappable batteries
CERTIFICATIONS	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI)
WARRANTY	
Product Warranty Period (U.S. & Canada)	1-year limited warranty
Product Warranty Period (International)	2-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	2-year limited warranty

Related Items

Required Products

Related Model	Description	Qty.
W05-BW1-247	3-Phase UPS System (20k, 30k & 40k) Start-Up and On-Site Warranty Service Programs	1
W05-BW1-247-1B	3-Phase UPS System (20k, 30k & 40k) Start-Up and On-Site Warranty Service Programs	1

Optional Products

Related Model	Description	Qty.
ENVIROSENSE	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	1
SNMPWEBCARD	For remote monitoring and control via SNMP, Web, or Telnet.	1
SUBF2030	External Battery Frame for Extended Runtime - Compatible with Select SmartOnline 20kVA & 30kVA 3-Phase UPS System	1
SURBC2030	Internal Battery Pack - Compatible with Select SmartOnline 20kVA & 30kVA 3-Phase UPS System	1
SU30KMBPK	3 Breaker Maintenance Bypass Panel for SU30K3/3, SU30K3/3XR5 and SU30K3/3INT	1
W05-EW1-247	3-Phase UPS System (20k, 30k & 40k) Start-Up and On-Site Warranty Service Programs	1
W05-EW1-247-1B	3-Phase UPS System (20k, 30k & 40k) Start-Up and On-Site Warranty Service Programs	1
W05-SCBAS1	3-Phase UPS System (20k, 30k & 40k) - Basic Warranty Service Contracts	1
W05-SCBAS1-1B	3-Phase UPS System (20k, 30k & 40k) - Basic Warranty Service Contracts - Includes primary battery cabinet plus one additional battery cabinet	1
W05-SCENH1	3-Phase UPS System (20k, 30k & 40k) - Premium Warranty Service Contracts	1
W05-SCENH1-1B	3-Phase UPS System (20k, 30k & 40k) - Premium Warranty Service Contracts - Includes primary battery cabinet plus one additional battery cabinet	1
SUDC208V42P	20-60kVA 3 Phase Power Distribution Center	1
SUDC208V42P30M	20-30kVA 3 Phase Power Distribution Center with Integrated 3 breaker 208V Service Bypass Switch	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3608.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.