



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: DTEL2

2-Line RJ11/RJ45 Network Surge Suppressor for Network/Phone Lines

Highlights

- RJ11/RJ45 2-line dial-up surge protector
- Protects against the effects of electrostatic discharge, faulty wiring and lightning



Description

Tripp Lite's DTEL2 surge suppressor is designed to protect data and communications equipment against AC transients caused by lightning, electrostatic discharge and ground surges that can enter equipment from the signal lines or chassis ground. The DTEL2 features RJ45/RJ11 plugs for modems, telephone lines and answering or fax machines.

Applications

- Ideal for modems, fax and answering machines

Package Includes

- DTEL2 dataline protector
- 5-in. RJ11 telephone patch cable
- Warranty information and instruction manual

Features

- Protects against the effects of electrostatic discharge, faulty wiring and lightning
- Comes with RJ11 telephone patch cable

Specifications

OVERVIEW	
Intended Application	Home/Office, Computer Networking
OUTPUT	
Circuit Breaker (amps)	250
INPUT	
Recommended Electrical Service	120V, 230V
Input connection type	RJ11/RJ45

UPC ASSIGNMENT	
Unit Carton UPC#	037332010865
SURGE / NOISE SUPPRESSION	
Clamping voltage (RMS)	260
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Additional Dataline Protection	4,5 & 3,6 pairs
PHYSICAL	
Style	Direct Plug-In
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=150.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.