



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SK5TEL-0

### 5 outlet, direct plug-in, 1080 joules, 1-line RJ 11 protection - Protect It! Surge Suppressor



#### Highlights

- 5 outlets / direct plug-in
- 1080 joule rating
- Tel/DSL Surge Protection
- Diagnostic LEDs
- \$15,000 Ultimate Lifetime Insurance (Valid US & Canada only)

#### Description

The SK5TEL-0 surge suppressor offers reliable surge and line noise protection. The compact direct plug-in design allows for easy portability and features 5 outlets and 1080 joules of surge energy absorption. Set of RJ11 telephone line suppression jacks protect dial-up and DSL modem lines, fax machines, cordless phones and more. Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged. \$15,000 Ultimate Lifetime Insurance (USA & Canada only).

#### Applications

- Ideal for any desktop, network or home computing application requiring AC power protection

#### Package Includes

- SK5TEL-0 surge suppressor
- 6-ft phone cord

#### Features

- 5 outlets / direct plug-in
- Surge suppression rating: 1080 joules
- 1 in/1 out Tel/DSL surge protection
- EMI/RFI noise filtering
- Diagnostic LEDs indicate Protected (green) & Grounded (red)
- \$15,000 Ultimate Lifetime Insurance (USA and Canada Only)

#### Specifications

OVERVIEW	
Intended Application	Home / Office
OUTPUT	
Frequency compatibility	60 Hz
Output watts	1875
Circuit Breaker (amps)	15

Outlet quantity / type	5 NEMA5-15R
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120v
Input connection type	NEMA 5-15P
Input plug features	120V, 15A
Input cord details	Direct plug-in
Voltage compatibility (VAC)	120
Maximum Surge Amps	72000
<b>UPC ASSIGNMENT</b>	
Unit Carton UPC#	037332167477
<b>SURGE / NOISE SUPPRESSION</b>	
AC suppression joule rating	1080
AC suppression response time	< 1ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
Clamping voltage (RMS)	150
UL1449 let through rating	500, 500, 400
EMI / RFI filtering	up to 45dB
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	Yes
<b>PHYSICAL</b>	
Unit Dimensions (HWD/in)	5 x 3.5 x 2.1
Unit Dimensions (HWD/cm)	12.7 x 8.89 x 5.33
Unit weight (lbs)	.33
Unit weight (kg)	.15
Material of construction	Plastic
Housing Color	Light Gray
Receptacle Color	Light Gray
Style	Direct plug-in
<b>CERTIFICATIONS</b>	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
cUL / CSA (Canada)	cUL
Approvals	RoHS
<b>WARRANTY</b>	

<b>Product Warranty Period (Worldwide)</b>	Lifetime limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$15,000 <a href="#">Ultimate Lifetime Insurance</a>

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4982](http://www.tripplite.com/en/products/model.cfm?txtModelID=4982).

---

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.