



**Tripp Lite**  
 1111 West 35th Street  
 Chicago, IL 60609 USA  
 Telephone: +(773) 869 1234  
 E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLP707TEL

### 7 outlet, 7-ft cord, 1080 joules, tel/modem protection - Protect It! Surge Suppressor



#### Highlights

- 7 outlets / 7-ft. cord
- 1080 joule rating
- 1 in/1 out tel/modem surge protection
- \$50,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's TLP707TEL surge suppressor offers complete AC and phone line surge suppression for comprehensive protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. Set of RJ11 telephone line suppression jacks protect dialup and DSL modem lines, fax machines, cordless phones and more. TLP707TEL offers 7 total outlets, 7 foot cord with space-saving angled plug, automatic cord management and diagnostic LEDs to warn of wiring problems and suppressor damage. Heavy grade AC suppression rated at 1080 joules shields equipment from surges and line noise. Attractive metallic silver housing with 3 designated transformer plug outlets offers convenient protection of desktop computer equipment and accessories. \$50,000 [Ultimate Lifetime Insurance](#) (USA and Canada Only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/7-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Unique on-end suppressor format supports the connection of up to 3 large transformer plugs on one side and 4 additional straight input plugs on the other

SUPPRESSION: AC: 150V RMS Clamping/1080 joules/400V UL1449 3rd Edition

#### Applications

- Ideal for home computers, TV/VCR/DVD players, stereos and lamps

#### Package Includes

- TLP707TEL surge suppressor
- 6-ft. RJ11 cable
- Instruction manual and warranty information

#### Specifications

<b>OVERVIEW</b>	
Intended Application	Home/Office
<b>OUTPUT</b>	

<b>Frequency compatibility</b>	50 / 60 Hz
<b>Output watts</b>	1800
<b>Circuit Breaker (amps)</b>	15
<b>Overload protection</b>	15A resettable combo switch / circuit breaker
<b>Outlet quantity / type</b>	7 NEMA 5-15R
<b>Transformer accommodation</b>	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 6 transformers total
<b>Outlet safety covers</b>	Includes built-in sliding outlet safety covers
<b>Outlet orientation</b>	Two rows of outlets, 3 widely spaced on one side for transformers, 4 closely spaced outlets on the other
<b>INPUT</b>	
<b>Nominal Input Voltage(s) Supported</b>	120V AC
<b>Recommended Electrical Service</b>	120V (110-125V)
<b>Input connection type</b>	NEMA 5-15P
<b>Input plug features</b>	Space-saving right angle input plug
<b>Input cord length (ft.)</b>	7
<b>Input cord length (m)</b>	2.13
<b>Input cord gauge, type</b>	14 gauge, SJT
<b>Voltage compatibility (VAC)</b>	120
<b>Maximum Surge Amps</b>	72000
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Switches</b>	Combination AC circuit breaker and 2 position on/off power switch
<b>Diagnostic LEDs</b>	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
<b>SURGE / NOISE SUPPRESSION</b>	
<b>AC suppression joule rating</b>	1080
<b>AC suppression response time</b>	< 1 ns
<b>Protection modes</b>	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
<b>Clamping voltage (RMS)</b>	150
<b>UL1449 let through rating</b>	400V
<b>EMI / RFI filtering</b>	Up to 20dB
<b>DATALINE SURGE SUPPRESSION</b>	
<b>Telephone/DSL Protection</b>	Yes
<b>Telephone/DSL Protection Details</b>	1 line
<b>Cable (Coax) Protection</b>	No

Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Shipping Dimensions (HWD/in)	12.40 x 4.92 x 2.25
Shipping Dimensions (HWD/cm)	31.50 x 12.50 x 5.72
Shipping weight (lbs)	1.41
Shipping weight (kg)	0.64
Unit Dimensions (HWD/in)	1.97 x 1.61 x 10.91
Unit Dimensions (HWD/cm)	5.00 x 4.09 x 27.71
Unit weight (lbs)	1.25
Unit weight (kg)	0.57
Material of construction	Plastic
Housing Color	Metallic Silver
Receptacle Color	Gray
AC line cord color	Black
Style	Strip
Form factors supported	Supports floor / desktop placement
Outlets center to center measurement	Transformer Side Spacing = 61.8mm; Standard Outlet Side Spacing = 25.4mm
<b>SPECIAL FEATURES</b>	
Appearance	Unique on-end suppressor format supports the connection of up to 3 large transformer plugs on one side and 4 additional straight input plugs on the other.
Right-Angle Plug	Yes
<b>CERTIFICATIONS</b>	
UL1449 3rd Edition (AC Suppression)	UL1449 3RD EDITION
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
FCC Part 68 (Communications)	FCC Part 68
cUL / CSA (Canada)	cUL
Industry Canada (Communications)	Industry Canada
Approvals	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

**Connected Equipment  
Insurance (U.S., Canada  
& Puerto Rico)**

\$50,000 [Ultimate Lifetime Insurance](#)

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2633](http://www.tripplite.com/en/products/model.cfm?txtModelID=2633).

---

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.