



Model #: PS712B

7 outlet, 12-ft cord, black strip - Power It! Power Strip



Highlights

- 7 outlets
- 12 ft power cord
- Illuminated on/off switch
- 15 amp circut breaker
- . Keyhold mounting slots

Description

Tripp Lite's PS712B power strip offers reliable, convenient and cost-effective power distribution for applainces, power tools, lighting and other electrical equipment. PS712B offers 7 total outlets, 12 foot cord. Attractive black housing with keyhole mounting slots and 1 designated transformer plug outlet. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket.

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/12 ft. AC line cord ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle) FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

Applications

• Offers a reliable convenient and cost-effective method of power distribution for appliances, power tools, lighting and other electrical equipment in home, office or worksite.

Package Includes

- PS712B Surge Suppressor
- Instruction manual and warranty information

Features

- 7 outlets / 12-ft cord
- · Attractive black housing
- EMI/RFI noise filtering
- Can accommodate 1 transformer without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting

Specifications

OVERVIEW		
Intended Application Home/Office		
OUTPUT		
Frequency compatibility	50 / 60 Hz	

Output watts	1800	
Circuit Breaker (amps)	15	
Outlet quantity / type	7 NEMA 5-15R	
Transformer accommodation	Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 4 transformers total	
Outlet orientation	Single row	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P	
Input cord length (ft.)	12	
Input cord length (m)	3.66	
Input cord gauge, type	14 gauge, SJT	
Voltage compatibility (VAC)	120	
Maximum Surge Amps	72000	
LEDS ALARMS & SWITCHES		
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (HWD/in)	13.78 x 4.92 x 2.36	
Shipping Dimensions (HWD/cm)	35.00 x 12.50 x 5.99	
Shipping weight (lbs)	1.92	
Shipping weight (kg)	0.87	
Unit Dimensions (HWD/in)	1.32 x 2.05 x 11.69	
Unit Dimensions (HWD/cm)	3.35 x 5.21 x 29.69	
Unit weight (lbs)	1.76	
Unit weight (kg)	0.80	
Material of construction	Plastic	
Integrated keyhole mounting tabs	Keyhole mounting slots enable wall mounting	
Receptacle Color	Black	
AC line cord color	Black	

Outlets center to center measurement Distance between standard outlets = 29mm; Distance between last standard outlet and transformer outlet 33mm Keyhole slot center to center measurement Distance between slots = 151mm; Distance between slot height = 24mm CERTIFICATIONS RoHS NOM (Mexico) NOM UL1363 (Power Tap) UL1363 cUL / CSA (Canada) cUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	Style	Strip	
measurement CERTIFICATIONS Additional International Approvals RoHS NOM (Mexico) NOM UL1363 (Power Tap) UL1363 cUL / CSA (Canada) cUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY		Distance between standard outlets = 29mm; Distance between last standard outlet and transformer outlet = 33mm	
Additional International Approvals NOM (Mexico) NOM UL1363 (Power Tap) UL1363 CUL / CSA (Canada) Exceeds IEEE 587 category A&B specifications WARRANTY		Distance between slots = 151mm; Distance between slot height = 24mm	
NOM (Mexico) NOM (Mexico) UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY	CERTIFICATIONS		
UL1363 (Power Tap) CUL / CSA (Canada) CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY		RoHS	
cUL / CSA (Canada) Approvals Exceeds IEEE 587 category A&B specifications WARRANTY	NOM (Mexico)	NOM	
Approvals Exceeds IEEE 587 category A&B specifications WARRANTY	UL1363 (Power Tap)	UL1363	
WARRANTY	cUL / CSA (Canada)	cUL	
	Approvals	Exceeds IEEE 587 category A&B specifications	
Product Warranty Period Lifetime limited warranty	WARRANTY		
(Worldwide)		Lifetime limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5372.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.