Model #: HTSWIVEL6

6 Rotatable Outlets, Direct plug-in, 1200 Joules, 1-line gold coaxial 1-line tel/modem protection - Surge Suppressor

Highlights

- 6 rotatable outlets
- Direct plug-in design
- 1200 joule rating
- 1 line tel/modem and 1-line gold coax (2.2GHz bandwidth) protection
- $50,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Description

 Tripp Lite's HTSWIVEL6 Home/Business Theater Surge Suppressor provides high-performance protection--1200 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 6 outlets, 1-line coaxial protection and 1-line tel/modem protection safeguard an entire home/business theater system. $50,000Ultimate Lifetime Insurance coverage (USA and Canada only). Includes two diagnostic LEDs, 6 ft. gold coaxial cable and 6 ft. phone cord.

Applications

- Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

Package Includes

- HTSWIVEL6 Surge Suppressor
- Instruction manual with warranty information
- 6 ft. gold coaxial cable
- 6 ft. phone cord

Features

- 6 rotatable outlets allow for easier plug connection and removal
- 1200 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 1 set of surge-protected Type F gold coaxial connectors (with included 6 ft. coaxial cable) safeguard components on cable, satellite or antenna line (2.2GHz bandwidth)
- 1 set of surge-protected tel/modem connectors (with included 6 ft. phone cord) safeguard personal video recorders (PVRs) on a single dial-up line
- 2 diagnostic LEDs alert user to protection and grounding status
- High-impact plastic housing (black) stands up to the most demanding environments
- Direct plug-in design converts two outlets into six by pluggin into any wall outlet
- $50,000 Ultimate Lifetime Insurance (USA and Canada Only)

Specifications

OVERVIEW

Intended Application	Audio/Video

OUTPUT

Frequency compatibility	60 Hz
Circuit Breaker (amps)	15
Outlet quantity / type	6 NEMA 5-15R
Outlet orientation	Rotatable

INPUT

Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P
Input cord length (m)	Direct plug-in
Input cord length details	Direct Plug-In
Voltage compatibility (VAC)	120
Maximum Surge Amps	60000

LEDS ALARMS & SWITCHES

Diagnostic LEDs	Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status

SURGE / NOISE SUPPRESSION

AC suppression joule rating	1200
AC suppression response time	< 1 ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
Clamping voltage (RMS)	400
UL1449 let through rating	400, 500, 500
EMI / RFI filtering	Up to 20 dB

DATALINE SURGE SUPPRESSION

Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	Yes
Cable (Coax) Protection Details	1 line
Network (Ethernet) Protection	No

PHYSICAL

Shipping Dimensions (HWD/in)	8.6 x 5.8 x 2.38
Shipping Dimensions (HWD/cm)	21.84 x 14.73 x 6.05
Shipping weight (lbs)	1.0

Shipping weight (kg)	0.45
Unit Dimensions (HWD/in)	6.25 x 4 x 2.25
Unit Dimensions (HWD/cm)	15.88 x 10.16 x 5.72
Unit weight (lbs)	0.6
Unit weight (kg)	0.27
Material of construction	Plastic
Receptacle Color	Black
Style	Direct plug-in
Outlets center to center measurement	29mm
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
cUL / CSA (Canada)	cUL
Approvals	RoHS
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	$50,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3618.