



Model #: TLP615

6-outlet, 15-ft cord, 790 joule strip - Protect It! Surge Suppressor



Highlights

- 6 outlet / 15-ft. cord
- 790 joule rating
- \$20,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Description

Tripp Lite's TLP615 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP615 offers 6 total outlets, 15 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 790 joules shields equipment from surges and line noise. Attractive gray suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (USA & Canada Only).

Applications

• Ideal for any desktop, network or home computing application requiring AC line protection

Package Includes

- TLP615 surge suppressor
- Instruction manual with warranty information

Features

- 6 outlets
- 15-ft. cord
- Surge suppression rating: 790 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green protection LED
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers
- Keyhole support for wall mounting
- · Lighted power switch
- \$20,000 Ultimate Lifetime Insurance (USA and Canada Only)

Specifications

OVERVIEW	
Intended Application	Home/Office
OUTPUT	

Frequency compatibility	60 Hz	
Output watts	1875	
Circuit Breaker (amps)	15	
Overload protection	15A resettable illuminated combo switch / circuit breaker	
Outlet quantity / type	6 NEMA 5-15R	
Transformer accommodation	Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 3 transformers total	
Outlet orientation	Single row of 6 outlets	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P	
Input cord length (ft.)	15	
Input cord length (m)	1.83	
Input cord gauge, type	14 gauge, SJT	
Voltage compatibility (VAC)	120	
Maximum Surge Amps	35500	
LEDS ALARMS & SWITCHES		
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	790	
AC suppression response time	< 1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS)	150	
UL1449 let through rating	500V	
EMI / RFI filtering	up to 20dB	
PHYSICAL		
Shipping Dimensions (HWD/in)	13.2 x 5.8 x 1.8	
Shipping Dimensions (HWD/cm)	33.53 x 14.73 x 4.57	
Shipping weight (lbs)	1.77	
Shipping weight (kg)	0.80	
Unit Dimensions (HWD/in)	10.8 x 1.85 x 1.23	

Unit Dimensions (HWD/cm)	27.43 x 4.70 x 3.12	
Unit weight (lbs)	1.60	
Unit weight (kg)	0.73	
Material of construction	Plastic	
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting	
Housing Color	Light Gray	
Receptacle Color	Light Gray	
AC line cord color	Light Gray	
Style	Strip	
Outlets center to center measurement	28.5mm	
Keyhole slot center to center measurement	Distance between slots = 101mm; Distance between slot height = 28mm	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd EDITION	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 Ultimate Lifetime Insurance	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5001.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.