



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLP66NET

### 6-outlet, 6-ft cord, 1080 joules, RJ45 protection - Protect It! Surge Suppressor



#### Highlights

- 6 outlets / 6-ft cord
- 1080 joule rating
- Ethernet surge protection
- \$25,000 [Ultimate Lifetime Insurance](#) (USA, Canada & Puerto Rico only)

#### Description

Tripp Lite's TLP66NET surge suppressor has 6 outlets, a 6-ft. cord and diagnostic LEDs. The unit has a surge suppression rating of 1080 joules to handle the strongest surges. Built-in RJ45 jacks prevent surges from damaging your network equipment (6-ft network cable included). \$25,000 [Ultimate Lifetime Insurance](#) (USA, Canada & Puerto Rico only).

#### Applications

Personal computers, modems, CAD/CAM/CAE workstations, network nodes, file servers, point-of-sale terminals and more.

#### Package Includes

- TLP66NET
- 6-ft. network cable
- Instruction manual with warranty information

#### Features

- 6 outlets with integrated child safety covers
- 6ft cord
- Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft. network cable included)
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch
- \$25,000 [Ultimate Lifetime Insurance](#) (USA, Canada & Puerto Rico only)

#### Specifications

OVERVIEW	
Intended Application	Home/Office, Computer Networks
OUTPUT	
Frequency compatibility	60 Hz

Output watts	1800
Circuit Breaker (amps)	15
Overload protection	15A resettable illuminated combo switch / circuit breaker
Outlet quantity / type	6 NEMA 5-15R
Transformer accommodation	Supports 2 large transformer plug accessories without covering remaining outlets, accepts up to 4 transformers total
Outlet safety covers	6
Outlet orientation	Block style with two rows of 3 outlets
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P
Input cord length (ft.)	6
Input cord length (m)	1.83
Input cord gauge, type	14 gauge, SJT
Voltage compatibility (VAC)	120
Maximum Surge Amps	72000
<b>LEDS ALARMS &amp; SWITCHES</b>	
Switches	Combination AC circuit breaker and 2-position red illuminated on/off power switch
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
<b>SURGE / NOISE SUPPRESSION</b>	
AC suppression joule rating	1080
AC suppression response time	< 1 ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
Clamping voltage (RMS)	150
UL1449 let through rating	400v
EMI / RFI filtering	Up to 40 dB
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	Yes
<b>PHYSICAL</b>	
Shipping Dimensions (HWD/in)	11.02 x 7.08 x 1.77

<b>Shipping Dimensions (HWD/cm)</b>	27.99 x 17.98 x 4.50
<b>Shipping weight (lbs)</b>	1.97
<b>Shipping weight (kg)</b>	0.89
<b>Unit Dimensions (HWD/in)</b>	1.5 x 4.23 x 8.29
<b>Unit Dimensions (HWD/cm)</b>	3.81 x 10.74 x 21.06
<b>Unit weight (lbs)</b>	1.32
<b>Unit weight (kg)</b>	0.60
<b>Material of construction</b>	Plastic
<b>Integrated keyhole mounting tabs</b>	Keyhole mounting tabs enable wall mounting
<b>Housing Color</b>	Light Gray
<b>Receptacle Color</b>	Dark Gray
<b>AC line cord color</b>	Light Gray
<b>Style</b>	Block
<b>Outlets center to center measurement</b>	Distance between standard outlets = 28.5; Distance between standard outlet and transformer outlet = 48.5mm
<b>Keyhole slot center to center measurement</b>	119mm
<b>SPECIAL FEATURES</b>	
<b>Right-Angle Plug</b>	No
<b>CERTIFICATIONS</b>	
<b>UL1449 3rd Edition (AC Suppression)</b>	UL1449 3rd Edition
<b>UL1363 (Power Tap)</b>	UL1363
<b>cUL / CSA (Canada)</b>	cUL
<b>Industry Canada (Communications)</b>	Industry Canada
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	Lifetime limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$25,000 <a href="#">Ultimate Lifetime Insurance</a>

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4840](http://www.tripplite.com/en/products/model.cfm?txtModelID=4840).

