



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: ISOBAR2-6

2-outlet, 6-ft cord, 1410 joule, All metal housing Isobar Surge Suppressor - Premium surge, spike and line noise protection

Highlights



- 2 outlets / 6-ft. cord
- 1410 joule rating
- All metal housing
- \$25,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

For more than 20 years, America's leading companies have trusted Tripp Lite's Isobar Premium surge and noise suppressors to protect sensitive computer, networking and telecom equipment. With more than 18 million satisfied customers, the Isobar remains the world's #1 selling premium surge suppressor. Loaded with a generous combination of high quality components, near indestructible all-metal case and enhanced noise filtration system, Isobars offer the highest level of protection. Robust surge suppression circuits with sine-wave tracking offer extreme levels of protection against the heaviest surge conditions exceeding IEEE 587 category A & B specifications and reducing 6,000V test surges to harmless levels under 35 volts. Isobar's unique protection system combines large toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors into a complete surge and EMI/RFI noise reduction system. ISOBAR2-6 offers 2 outlets with network-grade surge suppression rated at 1410 joules/48,000 amps. Widely spaced NEMA 5-15 outlets accommodate up to 2 large transformer plugs. Includes 6 foot AC line cord with space-saving angled input plug and keyhole mounting tabs.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 2 NEMA5-15R/6 ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz (Requires NEMA 5-15R wall receptacle)

SUPPRESSION: AC: 140V RMS Clamping/1410 joules/48,000 amps

FORMAT: Corded all-metal strip

Applications

- Ideal for premium protection of personal computers with peripherals, network and CAD/CAM/CAE workstations, internetworking accessories, telecommunications systems, point of sale equipment, audio/video and home theater systems in any home, office or industrial application.

Package Includes

- ISOBAR2-6 Surge Suppressor
- Set of 4 outlet safety covers
- Instruction manual with warranty information

Features

- Tripp Lite's ISOBAR is the world's #1 selling premium suppressor series with more than 18 million satisfied customers and a safety-tested history of 20+ years
- Robust surge suppression with sine-wave tracking protects against the heaviest of surge conditions, exceeding IEEE category A&B specifications and reducing 6,000V test surges to harmless levels less than 35 volts
- Multi-component suppression circuits combine toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors
- 2 AC outlets accommodate up to 2 large transformer plugs
- Network grade surge suppression rated at 1410 joules/48,000 amps
- Widely spaced outlets accommodate up to 2 large transformer plugs without blocking outlets

- Lighted power switch with integrated 12 amp circuit breaker offers power control and overload protection
- 6 foot AC line cord with space-saving angled input plug
- Keyhole mounting tabs for installation in a variety of applications
- 120V AC, 50/60Hz electrical compatibility
- \$25,000 [Ultimate Lifetime Insurance](#) (USA and Canada Only)

Specifications

| OVERVIEW | |
|-------------------------------------|---|
| Intended Application | Home/Office, Computer Networks |
| OUTPUT | |
| Frequency compatibility | 50 / 60 Hz |
| Output watts | 1410 |
| Circuit Breaker (amps) | 12 |
| Outlet quantity / type | 2 NEMA 5-15R |
| Transformer accommodation | Supports up to 2 large transformer plug accessories without covering remaining outlets |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input connection type | NEMA 5-15P input plug |
| Input plug features | Space-saving right angle input plug |
| Input cord length (ft.) | 6 |
| Input cord length (m) | 1.83 |
| Voltage compatibility (VAC) | 120 |
| Maximum Surge Amps | 60000 |
| LEDS ALARMS & SWITCHES | |
| Switches | Combination AC circuit breaker & 2 position red illuminated on/off switch |
| SURGE / NOISE SUPPRESSION | |
| AC suppression joule rating | 1410 |
| AC suppression response time | NM = 0 ns. CM = |
| Protection modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| Clamping voltage (RMS) | 140 |
| AC suppression surge current rating | 48,000 amps (24,000 NM / 24,000 CM) |
| AC suppression components used | Metal oxide varistors, toroidal balanced chokes, ferrite rod-core inductors and VHF capacitors. |
| Safe thermal fusing | Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences |
| UL1449 let through rating | 400V |

| | |
|---|---|
| IEEE587 Cat. A ringwave let through | Less than 35 volts |
| EMI / RFI filtering | 40-80 dB |
| Immunity | Conforms to IEE 587 / ANSI C62.41 |
| DATALINE SURGE SUPPRESSION | |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Shipping Dimensions (HWD/in) | 10 x 5.75 x 2.75 |
| Shipping Dimensions (HWD/cm) | 25.4 x 14.61 x 6.99 |
| Shipping weight (lbs) | 2 |
| Shipping weight (kg) | 0.91 |
| Unit Dimensions (HWD/in) | 2.5 x 5 x 3.5 |
| Unit Dimensions (HWD/cm) | 6.35 x 12.7 x 8.89 |
| Unit weight (lbs) | 1.6 |
| Unit weight (kg) | 0.73 |
| Material of construction | Metal |
| Integrated keyhole mounting tabs | Metal end caps are fitted with keyhole mounting tabs for wallmount installation |
| Housing Color | Light gray |
| Receptacle Color | Black |
| AC line cord color | Light Gray |
| Style | Strip |
| Outlets center to center measurement | Distance between vertical outlets = 38.66mm |
| Keyhole slot center to center measurement | Distance between horizontal tabs = 108.43mm; Distance between vertical tabs = 58.17mm |
| SPECIAL FEATURES | |
| Appearance | Rugged all-metal corded strip format with high quality duplex receptacles |
| Right-Angle Plug | Yes |
| CERTIFICATIONS | |
| UL1449 3rd Edition (AC Suppression) | Tested to UL1449 3rd Edition by ETL |
| cUL / CSA (Canada) | Approved for Canada by ETL |
| Approvals | Exceeds IEEE 587 category A&B specifications |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

**Connected Equipment
Insurance (U.S., Canada &
Puerto Rico)**

\$25,000 [Ultimate Lifetime Insurance](#)

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=97.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.