

Model #: TLP66RCG

6 outlet, 6-ft cord, 2100 joule, Remote Controlled ECO-Surge Home/Business Surge Suppressor



Highlights

- Keychain remote control turns GREEN energy saving outlets on/off
- 6 outlet/6-ft cord
- 2100 joules
- \$100,000 Ultimate Lifetime Insurance (USA and Canada only)

Description

Tripp Lite's TLP66RCG offers reliable, GREEN surge technology that protects your computer and peripherals, the environment and your wallet. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. Convenient, one-touch remote control turns green energy-saving outlets on and off. TLP66RCG has 6 total outlets, 6 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Network-grade AC suppression rated at 2100 joules shields equipment from surges and line noise. Attractive cool gray suppressor housing with keyhole mounting tabs and up to 4 transformer plug outlets offers convenient protection of desktop computer equipment and accessories. \$100,000 connected equipment insurance (USA and Canada Only).

Applications

Ideal for any desktop, network or home computing application requiring AC protection

Package Includes

- TLP66RCG ECO-SURGE Energy-Saving Surge Suppressor
- Owners Manual

Features

- Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals
- 433 MHz key chain remote turns GREEN outlets on/off through walls, doors and furniture from up to 75 ft. away
- 6 total AC outlets with room for 4 transformer plugs
- 4 "Remote/Power Save" GREEN outlets cut AC power to idle components when turned off via remote control perfect for intermittent use equipment like DVD players, gaming consoles, speaker systems, monitors, printers, lighting etc.
- Two "Switched/Always-On" outlets provide continuous power for devices such as DVRs (TiVo), cable and satellite boxes, modems, routers, external hard drives, cordless phones and fax machines
- 2100 joules of AC surge suppression shields equipment from the strongest surges and line noise
- · Lighted power switch with integrated 15 amp circuit breaker offers power control and overload protection
- Diagnostic LEDs confirm outlet grounding and surge suppression status
- · Attractive gray suppressor housing with keyhole mounting tabs allow versatile placement options
- \$100,000 Ultimate Lifetime Insurance (USA and Canada Only)

Specifications

Circuit Breaker (amps) 15 Outlet quantity / type 6 NEMA 5-15R Transformer accommodation up to 4 INPUT Nominal Input Voltage(s) 120V AC supported Input connection type L5-15 Input plug features Straight plug Input cond length (ft.) 6 Input cord length (m) 1.83 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Bulk-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression response Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No Notwork (Ethernet) Protection No PHYSICAL Shipping Dimensions 13,59 x 18,00 x 4,80 Shipping Dimensions 13,50 x 16,00 x 4,80 Shipping Dimensions 13,50 x 16,00 x 4,80 Shipping Dimensions 13,50 x 16,00 x 4,80	Intended Application	Green (Energy-Saving)
Frequency compatibility Circuit Breaker (amps) 15 Outlet quantity / type 6 NEMA 5-15R Transformer accommodation INPUT Nominal Input Voltage(e) Supported 120V AC Supported 120V AC Supported 120V (110-125V) Service Input connection type 15-15 Input connection type Input cord length (ft.) Input cord length (ft.) Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) IABARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red lituminated onloff power switch Diagnostic LEDs Builkin LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression joule rating LI-149 let through rating DATALINES SUPPRESSUPP EMPLOYED DATALINES UPPRESSUPP EMPLOYED SINGE (Fibrenet) Protection No Network (Ethernet) Protection No Shipping Dimensions (HWD/Icm)	OUTPUT	
Circuit Breaker (amps) 15 Outlet quantity / type 6 NEMA 5-15R Transformer accommodation INPUT Nominal Input Voltage(s) 120V AC supported Input cond length (ft.) 6 Input cord length (ft.) 6 Input cord length (ft.) 120 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Bulk in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) Input surge suppression Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Includes Full normal mode (H-N) and common mode (N-G / H-G) line surge suppressi	Output Watt Capacity (watts)	1800
Outlet quantity / type Fransformer accommodation INPUT Nominal input Voltage(s) Supported 120V AC Supported 120V (110-125V) Input connection type 15-15 Input plug features Straight plug Input cord length (ft.) Input cord length (ft.) Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Bilagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression response Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating AO, 400, 400 EMI / RFI filtering Dip to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/Inn) Shipping Dimensions (HWD/Inn) Signal AC Suppression (AR) Signal Dimensions (HWD/Inn) Signal AR) 120 AC Suppression 120 AR) 12	Frequency compatibility	60 Hz
Transformer accommodation INPUT Nominal Input Voltage(s) Supported 120V AC Supported 120V (110-125V) Service Input connection type L5-15 Input plug features Input cord length (ft.) 8 Input cord length (ft.) 8 Input cord length (ft.) 1.83 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Inguist LEDs Input cord length (ft.) Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression response Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No Network (Ethernet) Protection Sipping Dimensions (HWD/in) Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/in)	Circuit Breaker (amps)	15
Nominal Input Voltage(s) Supported Recommended Electrical Recommended Electrical Service Input connection type L5-15 Input plug features Straight plug Input cord length (ft.) 6 Input cord length (ft.) 1,83 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 30000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) AC suppression joule rating LC Suppression response Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating Up to 20db DATALINE SURGE SUPPRESSUP Telephone/DSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No Physical Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/in) Single Suppression Single Suppression Single Suppression Straight Single Suppression Straight Single Suppression Single Dimensions (HWD/in) Shipping Dimensions (HWD/in) Single Suppression Singl	Outlet quantity / type	6 NEMA 5-15R
Naminal Input Voltage(s) Supported 120V (10-125V) 120V (110-125V) 120V (110-	Transformer accommodation	up to 4
Recommended Electrical Services 120V (110-125V)	INPUT	
Input connection type	Nominal Input Voltage(s) Supported	120V AC
Input plug features Input cord length (ft.) 6 Input cord length (m) 1.83 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20tb DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No Network (Ethernet) Protection 13.19 x 6.30 x 1.89 KHWD/im) Dimensions (HWD/cm) 33.50 x 16.00 x 4.80 Shipping Dimensions (HWD/cm)		120V (110-125V)
Input cord length (ft.) 6 Input cord length (m) 1.83 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Bullt-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 33.50 x 16.00 x 4.80 Shipping Dimensions 33.50 x 16.00 x 4.80	Input connection type	L5-15
Input cord length (m) 1.83 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 33.50 x 16.00 x 4.80 HWD/em) AS 300 SURGE ALERS SUPPRESION 33.50 x 16.00 x 4.80	Input plug features	Straight plug
Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time Voltage through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/im) 33,50 x 16,00 x 4,80	Input cord length (ft.)	6
Voltage compatibility (VAC) 120 Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time < 1 ns	Input cord length (m)	1.83
Maximum Surge Amps 39000 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/icm) 33.50 x 16.00 x 4.80	Input cord gauge, type	14 gauge, SJT
Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 13.19 x 6.30 x 1.89 (HWD/cm) 23.50 x 16.00 x 4.80	Voltage compatibility (VAC)	120
Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time 2100 AC suppression response 2 Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 33.50 x 16.00 x 4.80 Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	Maximum Surge Amps	39000
Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red) SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 33.50 x 16.00 x 4.80 Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	LEDS ALARMS & SWITCHES	
SURGE / NOISE SUPPRESSION AC suppression joule rating 2100 AC suppression response time 21 ns Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 13.19 x 6.30 x 1.89 Shipping Dimensions (HWD/in) 33.50 x 16.00 x 4.80	Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch
AC suppression joule rating AC suppression response time Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 33.50 x 16.00 x 4.80	Diagnostic LEDs	
AC suppression response time <1 ns Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 13.19 x 6.30 x 1.89 Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	SURGE / NOISE SUPPRESSION	N
Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 13.19 x 6.30 x 1.89 Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	AC suppression joule rating	2100
UL1449 let through rating 400, 400, 400 EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 13.19 x 6.30 x 1.89 Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	AC suppression response time	< 1 ns
EMI / RFI filtering Up to 20db DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) 33.50 x 16.00 x 4.80	Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	UL1449 let through rating	400, 400, 400
Telephone/DSL Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	EMI / RFI filtering	Up to 20db
Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (HWD/in) Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	DATALINE SURGE SUPPRESS	ION
PHYSICAL Shipping Dimensions (HWD/in) 13.19 x 6.30 x 1.89 Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	Telephone/DSL Protection	No
Shipping Dimensions (HWD/in) 13.19 x 6.30 x 1.89 Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	Network (Ethernet) Protection	No
(HWD/in) Shipping Dimensions (HWD/cm) 33.50 x 16.00 x 4.80	PHYSICAL	
(HWD/cm)	Shipping Dimensions (HWD/in)	13.19 x 6.30 x 1.89
Shipping weight (lbs) 1.73	Shipping Dimensions (HWD/cm)	33.50 x 16.00 x 4.80
	Shipping weight (lbs)	1.73

Shipping weight (kg)	0.78
Unit Dimensions (HWD/in)	1.67 x 4.41 x 9.25
Unit Dimensions (HWD/cm)	4.24 x 11.20 x 23.50
Unit weight (lbs)	1.45
Unit weight (kg)	0.66
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
AC line cord color	Gray
Style	Strip
Outlets center to center measurement	Distance between "Remoted" outlets = 28.5mm; Distance between "Remoted" and "Switched" outlets = 50mm
SPECIAL FEATURES	
Green & high efficiency features	Power saving auto-shutoff ECO outlets
Right-Angle Plug	No
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$100,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4751.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.