



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLM1015NC

### Power It! Power Strip with 10 Outlets and 15-ft. Cord



#### Highlights

- 10 outlets spaced to accommodate transformers
- Illuminated on/off switch with cover
- 15-amp circuit breaker
- 15 ft. power cord
- Heavy-duty metal case
- Keyhole slots on removable mounting brackets

#### Description

Tripp Lite's Power It! TLM1015NC power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment. Includes 10 NEMA 5-15R outlets spaced to accommodate transformers, 15-foot AC power cord and keyhole slots on removable mounting brackets. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features heavy-duty metal case to stand up to the most demanding environments, illuminated power switch with transparent cover to prevent accidental shutoff and 15A integrated circuit breaker to prevent dangerous overloads.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 10 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: Corded power distribution strip

#### Applications

- Offers a reliable, convenient and cost-effective method of power distribution for appliances, power tools, lighting and other electrical equipment in home, office or worksite.
- Unfiltered electrical pass-through makes the power strip ideal for distributing alternate waveform UPS or generator power to connected equipment.

#### Package Includes

- TLM1015NC power strip
- Warranty information
- Instruction manual

#### Features

- Multi-outlet power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment
- Includes 10 NEMA 5-15R outlets spaced to accommodate transformers
- Illuminated on/off switch provides one-touch power control for connected equipment
- Transparent switch cover snaps tight to prevent accidental shutoff
- Convenient keyhole slots on removable brackets provide secure mounting options for a wide variety of surfaces and applications

- 15A power handling capacity with integrated circuit breaker
- 120V AC, 50/60Hz electrical compatibility
- 15-foot AC power cord
- Heavy-duty metal case provides maximum safety and durability
- UL certification

## Specifications

| <b>OVERVIEW</b>                           |  |
|---|--|
| <b>Intended Application</b>               | Computer Networks  |
| <b>OUTPUT</b>                             |  |
| <b>Frequency compatibility</b>            | 50 / 60 Hz   |
| <b>Output watts</b>                       | 1800   |
| <b>Circuit Breaker (amps)</b>             | 15   |
| <b>Overload protection</b>                | 15A circuit breaker  |
| <b>Outlet quantity / type</b>             | 10 NEMA 5-15R  |
| <b>Transformer accommodation</b>          | Outlets spaced to accommodate transformers                           |
| <b>Outlet orientation</b>                 | 10 outlets arranged in 2 rows and spaced to accommodate transformers |
| <b>INPUT</b>                              |  |
| <b>Nominal Input Voltage(s) Supported</b> | 120V AC  |
| <b>Recommended Electrical Service</b>     | 15A 120V   |
| <b>Input connection type</b>              | NEMA 5-15P   |
| <b>Input cord length (ft.)</b>            | 15   |
| <b>Input cord length (m)</b>              | 4.5  |
| <b>Input cord gauge, type</b>             | SJT 14AWG  |
| <b>Voltage compatibility (VAC)</b>        | 120  |
| <b>LEDS ALARMS &amp; SWITCHES</b>         |  |
| <b>Switches</b>                           | Illuminated on/off switch controls power to all outlets              |
| <b>Locking switch cover</b>               | Transparent switch cover snaps tight to prevent accidental shutoff   |
| <b>PHYSICAL</b>                           |  |
| <b>Shipping Dimensions (HWD/in)</b>       | 2.25 x 20.5 x 11   |
| <b>Shipping Dimensions (HWD/cm)</b>       | 5.7 x 52.1 x 28  |
| <b>Shipping weight (lbs)</b>              | 5.2  |
| <b>Shipping weight (kg)</b>               | 2.4  |
| <b>Unit Dimensions (HWD/in)</b>           | 17.5 x 4 x 2.25  |
| <b>Unit Dimensions (HWD/cm)</b>           | 44.5 x 10.2 x 5.7  |
| <b>Unit weight (lbs)</b>                  | 4.6  |

|  |  |
|--|--|
| <b>Unit weight (kg)</b>                          | 2.1  |
| <b>Material of construction</b>                  | Metal case   |
| <b>Integrated keyhole mounting tabs</b>          | Keyhole slots on removable brackets enable secure mounting to a variety of surfaces        |
| <b>Receptacle Color</b>                          | Light Gray   |
| <b>AC line cord color</b>                        | Light Gray   |
| <b>Style</b>                                     | Strip  |
| <b>Outlets center to center measurement</b>      | Distance between horizontal outlets = 71.45mm; Distance between vertical outlets = 38.90mm |
| <b>Keyhole slot center to center measurement</b> | Distance between end tabs = 462.30mm   |
| <b>CERTIFICATIONS</b>                            |  |
| <b>Additional International Approvals</b>        | Complies with RoHS (Restriction of Hazardous Substances Directive)                         |
| <b>UL1363 (Power Tap)</b>                        | UL1363   |
| <b>cUL / CSA (Canada)</b>                        | cUL  |
| <b>WARRANTY</b>                                  |  |
| <b>Product Warranty Period (Worldwide)</b>       | Lifetime limited warranty  |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3466](http://www.tripplite.com/en/products/model.cfm?txtModelID=3466).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.