

Model #: SPS415HGULTRA

4-outlet, Medical-Grade Power Strip with Surge Suppression for Use in Patient-Care Areas



Highlights

- Full UL 60601-1/60950-1 compliance
- Approved for use within 6-ft. of patient-care areas
- 4 outlets, 15-ft. cord with NEMA 5-15P hospital-grade plug
- 1410 joules of surge suppression
- 15A resettable circuit breaker
- Switchless design prevents accidental shutoff
- Integrated locking outlet safety covers guard against contact with unused outlets
- Diagnostic LED indicates that power is present and surge protected (with no ground faults or line/neutral reversals)
- US Patent # 7,375,939 & U.S. Patent No. 8,339,759

Description

The SPS415HGULTRA is the first Medical-Grade Outlet Strip with Surge Suppression and full UL 60601-1/60950-1 compliance. Tested to U.S. and Canadian safety standards, it is the first of its kind to be agency approved for use in patient-care areas, including physicians' offices, imaging centers, laboratories and more. The SPS415HGULTRA is ideal for protecting electrical equipment from damaging surges and spikes within patient vicinity. Features include switchless design to prevent accidental shutoff, four NEMA 5-15R-HG hospital-grade outlets with safety covers, 1410 joules of surge suppression, NEMA 5-15P-HG hospital-grade plug and 15A resettable circuit breaker.

Applications

- AC power distribution surge suppression with hospital-grade receptacles and plug in healthcare applications where durability and reliability are required, including areas where NEC requires hospital-grade receptacles
- Patient rooms, treatment rooms, exam rooms, etc.

Package Includes

- SPS415HGULTRA Medical-Grade Outlet Strip wtih Surge Suppression
- Owner's manual with warranty information

Features

- Surge protection
- Approved for use in Patient-Care Areas
- Rugged all-metal housing stands up to the most demanding environments
- 4 x NEMA 5-15R-HG outlets with safety covers
- 1410 joules of surge suppression
- 15-ft. cord with NEMA 5-15P-HG plug
- Switchless design prevents accidental shutoff
- 15A circuit breaker
- Multiple installation options with integral mounting flanges and slots
- UL60601-1 and UL 60950-1 compliant
- U.S. Patent No. 7,375,939 & U.S. Patent No. 8,339,759

Specifications

OVERVIEW			
Intended Application	Hospital/Medical		
Model Type	For Patient-Care Areas		
OUTPUT			
Frequency compatibility	50 / 60 Hz		
Circuit Breaker (amps)	15		
Overload protection	15A resettable circuit breaker		
Outlet quantity / type	4 NEMA 5-15R-HG		
Outlet safety covers	Yes		
Outlet orientation	Single row of 4		
INPUT			
Nominal Input Voltage(s) Supported	120V AC		
Recommended Electrical Service	15A 120V		
Input connection type	NEMA 5-15P-HG		
Input cord length (ft.)	15		
Input cord length (m)	4.572		
Voltage compatibility (VAC)	120		
Maximum Surge Amps	60000		
LEDS ALARMS & SWITCHES			
LED Indicators	Proper wiring and surge protection working		
SURGE / NOISE SUPPRESSION			
AC suppression joule rating	1410		
PHYSICAL			
Unit Dimensions (HWD/in)	1.5 x 13.75 x 2.5		
Unit Dimensions (HWD/cm)	3.8 x 34.9 x 6.4		
Unit weight (lbs)	3.2		
Unit weight (kg)	1.5		
Material of construction	Metal		
Integrated keyhole mounting tabs	Yes		
Receptacle Color	White		
AC line cord color	White		
Style	Strip		
SPECIAL FEATURES			
Appearance	Attractive all-white color scheme		
CERTIFICATIONS			

Approvals	TUV tested to UL 60601-1 and UL 60950-1 (USA); TUV tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 (Canada)		
WARRANTY			
Product Warranty Period (Worldwide)	Lifetime limited warranty		

Related Items

Optional Products

Related Model	Description	Qty.
PSCLAMP	Power Strip Mounting Clamp	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4843.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.