

Model #: RBC36-SLT

UPS Replacement Battery Cartridge for select Tripp Lite SLT UPS



Highlights

- Tripp Lite-certified premium battery cartridge
- Pre-assembled and wired battery kit offers simple installation
- Rugged leak-proof construction
- Maintenance free
- Wide operating temperature range

Description

Tripp Lite's premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery cartridge is carefully screened and certified to meet or exceed original specifications, and ships ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. See Tripp Lite's UPS replacement battery web page to confirm compatibility and quantity required.

Compatible with Tripp Lite models SMART1500SLT, SMX1500SLT (versions with pre-assembled 3-battery cartridges only; see compatibility listing for non-assembled battery versions)

Package Includes

• One pre-assembled battery pack consisting of three 12V batteries

Features

- Restores UPS runtime performance to original specifications
- Comes pre-assembled and ready for installation
- Reusable packaging holds expired batteries for recycling center delivery

Specifications

| BATTERY | |
|------------------------------|--|
| DC system voltage (VDC) | 36 |
| Included Battery Set | Set of 3 pre-assembled 12V batteries |
| Typical battery lifespan | 3-5 years, depending on UPS operating conditions |
| PHYSICAL | |
| Shipping Dimensions (HWD/in) | 7.8 x 9.8 x 11.8 |

| Shipping Dimensions (HWD/cm) | 19.8 x 25 x 30 |
|--|---------------------------------------|
| Shipping weight (lbs) | 20.6 |
| Shipping weight (kg) | 9.3 |
| Unit Dimensions (HWD/in) | 4 x 6 x 7.5 |
| Unit Dimensions (HWD/cm) | 10.16 x 15.2 x 19.1 |
| Unit weight (lbs) | 18.8 |
| Unit weight (kg) | 8.5 |
| ENVIRONMENTAL | · · · · · · · · · · · · · · · · · · · |
| Relative Humidity | 0-95% NON-CONDENSING |
| Operating Elevation (ft.) | 0-10,000 FEET |
| Storage Elevation (ft.) | 0-50,000 FEET |
| Operating Elevation (m) | 0-3000 m |
| Storage Elevation (m) | 0 - 15,200 m |
| CERTIFICATIONS | |
| Certifications | RoHS compliant |
| WARRANTY | |
| Product Warranty Period (U.S. & Canada) | 18-month limited warranty |
| Product Warranty Period (International) | 1-year limited warranty |
| Product Warranty Period (Mexico) | 1-year limited warranty |
| Product Warranty Period (Puerto Rico) | 1-year limited warranty |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3560.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.