



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: RBC96-3U

### 3U UPS Replacement Battery Cartridge for select Tripp Lite SmartOnline UPS

#### Highlights

- Tripp Lite-certified premium battery cartridge
- Pre-assembled and wired battery kit offers simple installation
- Rugged leakproof construction
- Maintenance free
- Wide operating temperature range



#### Description

Tripp Lite's premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery cartridge is carefully screened and certified to meet or exceed original specifications, and ships ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. See Tripp Lite's UPS replacement battery web page to confirm compatibility and quantity required.

COMPATIBLE WITH TRIPP LITE MODELS SU3000RTXL3U, SU3000RTXR3U, SU3000XL (versions with pre-assembled 6-battery cartridges only; see compatibility listing for non-assembled battery versions)

#### Package Includes

- One pre-assembled battery pack consisting of six 12V batteries

#### Features

- Restores UPS runtime performance to original specifications
- Comes pre-assembled and ready for installation
- Reusable packaging holds expired batteries for recycling center delivery

#### Specifications

BATTERY	
DC system voltage (VDC)	72
Included Battery Set	6 pre-assembled 12V batteries
Typical battery lifespan	3 to 5 years, depending on UPS operating conditions
PHYSICAL	
Shipping Dimensions (HWD/in)	8.8 x 11.8 x 16.0

<b>Shipping Dimensions (HWD/cm)</b>	22.2 x 40.6 x 29.8
<b>Shipping weight (lbs)</b>	39.7
<b>Shipping weight (kg)</b>	18.0
<b>Unit Dimensions (HWD/in)</b>	4.0 x 6.0 x 15.5
<b>Unit Dimensions (HWD/cm)</b>	10.2 x 39.4 x 15.2
<b>Unit weight (lbs)</b>	37.0
<b>Unit weight (kg)</b>	16.8
<b>ENVIRONMENTAL</b>	
<b>Relative Humidity</b>	0-95% non-condensing
<b>Operating Elevation (ft.)</b>	10,000 ft.
<b>Storage Elevation (ft.)</b>	10,000 ft.
<b>Operating Elevation (m)</b>	3,000 m
<b>Storage Elevation (m)</b>	3000 m
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S. &amp; Canada)</b>	18-month limited warranty
<b>Product Warranty Period (International)</b>	1-year limited warranty
<b>Product Warranty Period (Mexico)</b>	1-year limited warranty
<b>Product Warranty Period (Puerto Rico)</b>	1-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3099](http://www.tripplite.com/en/products/model.cfm?txtModelID=3099).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.