



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SUPDMB710IEC

**Detachable PDU option with IEC output connections for compatible SmartOnline UPS Systems**



### Highlights

- Converts compatible SmartOnline high-voltage UPS systems to provide worldwide compatible output connections
- For use with input voltages of 200-240 VAC
- Hardwired input/ 6 IEC320 C19 output connections
- Manual bypass feature ensures maximum equipment availability

### Description

The SUPDMB710IEC converts the output of our SmartOnline SU8000RT3U and SU10000RT3U to worldwide output connections. Manual bypass feature ensures maximum availability of connected equipment while UPS maintenance occurs. Can accept input voltages of 200-240 VAC. Hardwire input/ 6 IEC320 C19 output connections.

#### Applications

- Ideal for use with Tripp Lite's SU8000RT3U and SU10000RT3U UPS systems in 200-240V applications where hardwire input/ C19 output connections are required

#### System Requirements

- For use with SmartOnline SU8000RT3U and SU10000RT3U Rack/Tower UPS systems in applications requiring a detachable PDU with manual bypass

#### Package Includes

- SUPDMB710IEC detachable PDU
- Mounting hardware
- Owner's Manual with warranty instructions

### Specifications

OVERVIEW	
Model Type	Outlet Kits
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output nominal voltage	200/208/220/230/240 VAC
Overload protection	6 double-pole 20A circuit breakers

<b>Outlet quantity / type</b>	6 IEC320 C19
<b>INPUT</b>	
<b>Nominal Input Voltage(s) Supported</b>	200V AC; 208V AC; 230V AC; 240V AC; 220V AC
<b>Input connection type</b>	Hardwire
<b>Voltage compatibility (VAC)</b>	200; 208; 220; 230; 240
<b>PHYSICAL</b>	
<b>Shipping Dimensions (HWD/in)</b>	12.25 x 9.25 x 8.25
<b>Shipping Dimensions (HWD/cm)</b>	31.1 x 23.5 x 21
<b>Shipping weight (lbs)</b>	9.9
<b>Shipping weight (kg)</b>	4.5
<b>Unit Dimensions (HWD/in)</b>	10.25 x 7.5 x 6.5
<b>Unit Dimensions (HWD/cm)</b>	26 x 19.1 x 16.5
<b>Unit weight (lbs)</b>	7.9
<b>Unit weight (kg)</b>	3.6
<b>Material of construction</b>	Sheet metal
<b>SPECIAL FEATURES</b>	
<b>Appearance</b>	All-black color scheme
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL1778 (USA), CSA (Canada), CE (Europe)
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	2-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4029](http://www.tripplite.com/en/products/model.cfm?txtModelID=4029).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.