



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: 0SU60020

Minicom Power-on-Cable (PoC)

Highlights



- Seamless integration with Minicom PX and IP Control remote access units
- Modular design allows expandability
- 90-260 VAC / 44-66 Hz international coverage
- Current consumption up to 10A
- Flexible power redundancy
- Unique design & 0U footprint
- Easy 3rd party integration with open standard protocol
- Galvanic Separation - no physical connection between management and power device
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

Completing the OOB Remote Support package

The Power-on-Cable (PoC) is a Single Port Power Control (SPPC) unit that enables remote power control (power on/off/reboot) of a connected device. The PoC is used in conjunction with Minicom's line of PX and IP Control remote access units, which together provide the complete remote support package. The PoC is serially controlled via the Minicom remote access unit, thus preventing costly mistakes and ensuring the power commands are sent only to the required device.

Maximizing power efficiency

The PoC is targeted at any IT environment that includes mission critical computers, servers or network and monitoring devices, which require 24/7 remote power management to ensure systems are up and running at all times. These include computer rooms, server rooms, data centers, production lines, distributed intelligent devices, industrial applications and more. Minicom's PoC solves the problem of power control to remote IT infrastructure in cases where a PDU cannot provide enough electrical current or when the number of ports are not optimized to the application.

Unique "power cord" design

Its unique and robust "power cord" design meets the stringent requirements of cable management in IT environments and make it extremely easy to slide several units together and control several devices through the same interface.

System Requirements

- Minicom KVM

Package Includes

- For use with PX (Model #0SU70028) and IP Control (Model #0SU70017) remote access units

Features

- Seamless integration with Minicom KVM and IP devices
- Modular design allows expandability
- 90-260 VAC / 44-66 Hz international coverage
- Current consumption up to 10A
- Flexible power redundancy
- Unique design & 0U footprint
- Easy 3rd party integration with open standard protocol
- Galvanic Separation - no physical connection between management and power device
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
Model Type	Interface Modules
UPC ASSIGNMENT	
Unit Carton UPC#	654518211429
PHYSICAL	
Color	Black
ENVIRONMENTAL	
Storage Temperature Range	-15 to 50 C / 5 to 122 F
Relative Humidity	0 to 95%
Operating Temperature	0 to 50 C / 32 to 122 F
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
0SU70028	Minicom PX USB - Remote KVM access	1
0SU70068	Minicom PX USB - Remote KVM access with Power-on-Cable (POC)	1
0SU70017	Minicom IP Control - Remote BIOS Access	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5205.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.