



Model #: B140-1P0-WP

DVI Over Cat5 Passive Extender Remote Wallplate



Highlights

- For use with B140-002 or B140-004 extender/splitter transmitter units
- \bullet Supports DVI-D Single-Link video resolutions up to 1920 x 1080 @ 60Hz
- Extends a 1920 x 1080 @ 60Hz signal up to 50 ft., or a 1024 x 768 @ 60Hz signal up to 100 ft.
- Use 24AWG, Solid Wire Cat5e/6 cable, such as Tripp Lite's N202-Series, to achieve maximum distance and resolution
- Compatible with all operating systems
- Plug and play, no external power, software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

The B140-1P0-WP is a receiver wallplate that is used with the B140-002 and B140-004 extender/splitter transmitter units, and it transmits a DVI-D Single-Link signal up to 100 ft. away using a single Cat5e/6 patch cable. To achieve maximum distance and resolution, use 24AWG Solid Wire Cat5e/6 cable (Tripp Lite'sN202-Series). The B140-1P0-WP is compatible with all operating systems, and is plug and play, with no external power, software or drivers required. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Installation is simple. Connect a B140-002 or B140-004 transmitter (not included) to a DVI source using a Tripp Lite P561-Series DVI cable (not included). Connect the B140-1P0-WP to a display using a Tripp Lite P561-Series DVI cable (not included). Finally, the receiver unit is connected to an RJ45 port on the transmitter unit using a single Cat5e/6 cable. A 1920 x 1080 @ 60Hz signal can be extended up to 50 ft. from the source,, or a 1024 x 768 @ 60Hz signal up to 100 ft..

Package Includes

- B140-1P0-WP DVI Over Cat5 Passive Extender Remote Wallplate
- Wallplate screws
- 110 punchdown tool
- Owner's manual

Features

- Transmit a DVI-D Single-Link signal up to 100 ft. away using a single Cat5e/6 patch cable
- For use with B140-002 or B140-004 extender/splitter transmitter units
- Supports DVI-D Single-Link video resolutions up to 1920 x 1080 @ 60Hz
- Extends a 1920 x 1080 @ 60Hz signal up to 50 ft., or a 1024 x 768 @ 60Hz signal up to 100 ft.
- Use 24AWG, Solid Wire Cat5e/6 cable, such as Tripp Lite's N202-Series, to achieve maximum distance and resolution
- HDCP compatible
- Compatible with all operating systems
- Plug and play; no external power, software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Specifications

OVERVIEW		
Cable Type	DVI	

Display Style	Splitter		
PHYSICAL			
Unit Dimensions (HWD/in)	4.5 x 2.75 x 1		
Unit Dimensions (HWD/cm)	11.43 x 6.99 x 2.54		
Mounting accessories included	Yes		
CONNECTIONS			
Connector A	(10) PROUDO (10) PATA (10) (10) (10) (10) (10) (10) (10) (10)		
Connector B	DVI-I (FEMALE)		
WARRANTY			
Product Warranty Period (Worldwide)	1-year limited warranty		

Related Items

Required Products

Related Model	Description	Qty.
B140-002	DVI over Cat5 Extender/Splitter, 2-Port Local Transmitter Unit	1
B140-004	DVI over Cat5 Extender/Splitter, 4-Port Local Transmitter Unit	1

Recommended Products

Related Model	Description	Qty.
N022-01K-GY	1000-ft. Cat5e 350MHz Bulk Solid-core PVC Cable - Gray	1
N222-01K-GY	1000-ft. Cat6 Gigabit Bulk Solid PVC Cable - Gray	1
N046-000	110/66 Punch Down Installation Tool for Cat6a/Cat6/Cat5e/Cat5/Network Cable	1

Optional Products

Related Model	Description	Qty.
N202-025-BL	25-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-050-BL	50-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-075-BL	75-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-100-BL	100-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
P561-006	6-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1
P561-010	10-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1
B140-1A0	DVI Over Cat5 Active Extender Remote Unit	1
B140-1A0-WP	DVI Over Cat5 Active Extender Remote Wallplate	1
B140-1P0	DVI Over Cat5 Passive Extender Remote Unit	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4602.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.