



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: N785-001-SC

### Fiber Optic - 10/100/1000BaseT to 1000BaseFX-SC Gigabit Media Converter

#### Highlights



- Convert UTP Gigabit Ethernet to Fiber
- Supports Auto MDI / MDI-X
- Half or Full Duplex Operation
- Auto-Senses 10 / 100 / 1000

#### Description

Tripp Lite's N785-001-SC, 10/100/1000 Gigabit Media Converter, is an economical way to extend the distance ( up to 2Km ) of network nodes by converting Cat5/6 UTP cables to Fiber Optic. The Media Converter features automatic MDI/MDI-X configuration, and the UTP port senses the network speed automatically as well. Supports half or full duplex operation on the fiber port. Power supplied by external AC adapter.

#### Applications

- Remote network nodes that are beyond the 100 meter distance limitation of UTP

#### Package Includes



- N785-001-SC 10/100/1000BaseT to 1000BaseFX Gigabit Media Converter
- External Power Supply ( Input: 110-265V, 50/60Hz, 0.2A / Output: 5V, 2A )
- Owners Manual

#### Features

- Connect 10BaseT/100BaseT /1,000BaseT UTP Ethernet to 1000BaseFX Fiber Ethernet
- Auto MDI/MDI-X
- UTP port auto-senses network speed
- Fiber lengths up to 2Km
- 6 LED Function lights
- Uses 62.5/125 or 50/125 Multimode cable
- 3.75"L x 2.75"W x 1"H
- Wavelength: 1310nm

#### Specifications

OVERVIEW	
Model Type	Converters
CONNECTIONS	

<b>Connector A</b>	 RJ45 (FEMALE)
<b>Connector B</b>	 SC (FEMALE)
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	1-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4485](http://www.tripplite.com/en/products/model.cfm?txtModelID=4485).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.