



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

- In most applications, a signal booster ([B120-000-SL](#)) should be used with this cable to ensure a signal strong enough for your display.
- An alternate solution is to use a Tripp Lite DVI over Cat5 Extender ([B140-101X](#)) in place of a 50 ft. DVI cable and signal booster.

Model #: P561-050

50-ft. DVI Single Link TMDS Cable (DVI-D M/M)



Highlights

- For use with Single Link TMDS specified equipment
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 1920 x 1200
- High Speed Digital Transmission to 9.9Gbps
- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection

Description

Tripp Lite's 50-ft. DVI Single Link TMDS cable delivers the high performance, high bandwidth needed for today's digital video displays. Gold plated contacts ensure excellent conductivity, while double shielding (foil and braid) provides maximum EMI/RFI protection. Use in conjunction with DVI video cards that are specified as Single Link. Both DVI connectors are molded, have integral strain relief for long life reliability, and ferrite collars to drain off extraneous electrical interference. In most applications, a signal booster ([B120-000-SL](#)) will need to be used with this cable to ensure a signal strong enough for your display.

System Requirements

- DVI monitor and computer

Package Includes

- 50-ft. DVI Single Link TMDS Cable (DVI-D M/M)

Features

- For use with Single Link TMDS specified equipment
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 1920 x 1200
- High Speed Digital Transmission to 9.9Gbps
- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection
- In most applications, a signal booster ([B120-000-SL](#)) will need to be used with this cable to ensure a signal strong enough for your display

Specifications

| OVERVIEW | |
|----------------------|------------------------|
| Intended Application | Connecting Peripherals |
| Cable Type | DVI |

| | |
|-------------------------------------|---|
| Display Style | Direct Connect |
| Model Type | DVI |
| INPUT | |
| Cable Length (ft.) | 50 |
| Cable Length (m) | 15.24 |
| UPC ASSIGNMENT | |
| Unit Carton UPC# | 037332130877 |
| PHYSICAL | |
| Color | Black |
| Style | DVI |
| CONNECTIONS | |
| Connector A |  DVI-D SINGLE LINK (MALE) |
| Connector B |  DVI-D SINGLE LINK (MALE) |
| Number of Connectors | 2 |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

Related Items

Optional Products

| Related Model | Description | Qty. |
|--------------------------|--|------|
| B120-000 | DVI Dual Link Signal Extender (DVI F/F) | 1 |
| P120-000 | DVI Male to VGA Female Adapter (Analog DVI-M to HD15F) | 1 |
| P126-000 | DVI Female to VGA Male Adapter (Analog DVI-F to HD15M) | 1 |
| P560-006 | 6-ft. DVI Dual Link TDMS Cable (DVI-D M/M) | 1 |
| P560-010 | 10-ft. DVI Dual Link TDMS Cable (DVI-D M/M) | 1 |
| P561-006 | 6-ft. DVI Single Link TMDS Cable (DVI-D M/M) | 1 |
| P562-006 | 6-ft. DVI Dual Link Extension TDMS Cable (DVI-D M/F) | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3338.