- In most applications, a signal booster (B120-000-SL) should be used with this cable to ensure a signal strong enough for your display.
- An alternate solution is to use a Tripp Lite DVI over Cat5 Extender (B140-101X) in place of a 50 ft. DVI cable and signal booster.

Model #: P561-050-EZ

50-ft. Easy Pull All-in-One DVI Single Link Cable (DVI-D M/M)

Highlights

- Two-piece design runs through conduit or other tight areas
- Threaded circular DIN connector provides secure reattachment
- For use with Single Link TMDS specified equipment
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 1920 x 1200
- High Speed Digital Transmission to 9.9Gbps
- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection

Description

Tripp Lite's 50 ft. DVI-D Single Link Easy Pull All-in-One Monitor Cable makes running long length video cables a snap. The pull-apart design allows the cable to be run through conduit or other tight areas that a DVI connector wouldn't fit through. Diameter of the circular DIN end is only 7/8". Circular Easy Pull connector is threaded to ensure maximum security once the cable is reattached. Use in conjunction with DVI video cards that are specified as Single Link. DVI connectors are molded, have integral strain relief for long life reliability, and a ferrite collar to drain off extraneous electrical interference. In most applications, a signal booster (B120-000-SL) will need to be used with this cable to ensure a signal strong enough for your display.

Applications

- Suspended ceilings, walls, conduit or anywhere too small to pull a standard DVI cable through.

Package Includes

- 50-ft. Easy Pull All-in-One DVI Single Link Cable (DVI-D M/M)

Features

- Two-piece design runs through conduit or other tight areas
- Threaded circular DIN connector provides secure reattachment
- For use with Single Link TMDS specified equipment
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 1920 x 1200
- High Speed Digital Transmission to 9.9Gbps
- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection
- In most applications, a signal booster (B120-000-SL) will need to be used with this cable to ensure a signal strong enough for your display

Specifications

OVERVIEW

Intended Application	Connecting Peripherals
Cable Type	DVI
Display Style	Easy Pull

INPUT

Cable Length (ft.)	50
Cable Length (m)	15.24

UPC ASSIGNMENT

Unit Carton UPC#	037332142290

PHYSICAL

Color	Black
Style	Video Cables

CONNECTIONS

Connector A	 DVI-D SINGLE LINK (MALE)
Connector B	 DVI-D SINGLE LINK (MALE)
Number of Connectors	2

WARRANTY

Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
B120-000	DVI Dual Link Signal Extender (DVI F/F)	1
P162-000	DVI-I Gender Changer (DVI-I F/F)	1
P501-050	50-ft. SVGA/VGA Easy-Pull Gold Monitor Extension Cable with RGB Coax, (HD15 M/F)	1
P501-100	100-ft. SVGA/VGA Easy Pull Gold Monitor Extension Cable with RGB Coax, (HD15 M/F)	1
P503-050	50-ft. Easy Pull All-in-One SVGA/VGA Monitor Cable with Connectors, (HD15 M/M)	1
P503-100	100-ft. Easy Pull All-in-One SVGA/VGA Monitor Cable with RGB Coax, (HD15 M/M)	1
P561-100	100-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at

www.tripplite.com/en/products/model.cfm?txtModelID=3772.