Model #: P950-36I

36-inch eSATA (SATA-II) External Signal Cable (7Pin/7Pin)

Highlights

- Connect your high-speed eSATA device to a eSATA controller
- Support data transfer rates of up to 6Gbps
- Cable is double-shielded to protect against EMI/RFI

Description

Tripp Lite expands its line of hard drive cables with the introduction of our new line of eSATA (SATA II) cables. This 36" data cable connects any high speed eSATA drive, PVR/DVR, or SETOP box to an eSATA controller. SATA-II delivers higher data transfer rates (up to 6 Gbps), and the double-shielded cable design is perfect for the new generation of External SATA -II drives. SATA-II drives offer 6 times the transfer rate of USB & Firewire external drives. These cables feature 7-pin straight latching (Male) and offer easy installation.

Applications

- External eSATA devices, such as Hard Drives, PVR/DVR's, or SETOP boxes to a eSATA controller card

System Requirements

- eSATA Device
- eSATA Controller

Package Includes

36inch (3ft) eSATA (SATA-II) External Signal Cable (7Pin/7Pin)

Features

- Connect your high-speed eSATA device to an eSATA controller
- Support data transfer rates of up to 6 Gbps
- 36" Cable is double-shielded to protect against EMI/RFI
- RoHS Compliant

Specifications

OVERVIEW	
Intended Application	Connecting Peripherals
Cable Type	SATA
INPUT	

Cable Length (in.)	36

UPC ASSIGNMENT

Unit Carton UPC#	037332130969

PHYSICAL

Color	Blue
Style	SATA

CONNECTIONS

Connector A	 7 PIN ESATA (MALE)
Connector B	 7 PIN ESATA (MALE)
Number of Connectors	2

WARRANTY

Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
P940-39I	39-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin)	1
P944-06I	6-inch Serial ATA (SATA) Power Cable (4Pin to 15pin)	1
P946-12I	12-inch Serial ATA (SATA) Dual Power Adapter Cable (4pin/2x15pin SATA)	1
P950-18I	18-inch eSATA (SATA-II) External Signal Cable (7Pin/7Pin)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at
www.tripplite.com/en/products/model.cfm?txtModelID=3340.