



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: N422-10M

10M (33-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC)

Highlights



- 10 Meter LC/ST Mode Conditioning Cable
- 62.5/125 and 8.3/125
- Run 1000Base-LX Gigabit Ethernet over MMF by offsetting signal loss
- IEEE 802.3z Gigabit Ethernet Compliant

Description

Tripp Lites Mode Conditioning Cables are designed for use in Gigabit Ethernet 1000BASE-LX applications. They are fully compliant with IEEE 802.3z application standards. Mode Conditioning Cables are needed in applications where new high-speed Gigabit 1000BASE-LX routers and switches are being deployed into existing multimode plants. The need for this patch cord is due to the single-mode launch nature of the -LX or long-wave (1300 nm) transceiver modules used for Gigabit Ethernet. Launching a single-mode laser into the center of a multimode fiber can cause multiple signals to be generated that confuses the receiver at the other end of the fiber. These multiple signals, caused by Differential Mode Delay (DMD) effects, severely limit the cable distance lengths for operating Gigabit Ethernet. A mode conditioning patch cord eliminates these multiple signals by allowing the single-mode launch to be offset away from the center of a multimode fiber.

Applications

- Use when connecting a LX type fiber transceiver (Singlemode light) to a Multimode backbone

Package Includes

- 10 Meter LC/ST Mode Conditioning Cable

Features

- Use Singlemode Transceivers on Multimode Fiber Backbones
- 62.5/125 and 8.3/125
- Offsets the Singlemode Laser launch from the center of a Multimode fiber
- Available in a variety of connector combinations

Specifications

| | |
|----------------------|-------------------------------|
| OVERVIEW | |
| Intended Application | Computer Networking (Fiber) |
| Cable Type | MODE CONDITIONING FIBER OPTIC |
| INPUT | |

| | |
|-------------------------------------|---|
| Cable Length (m) | 10 |
| UPC ASSIGNMENT | |
| Unit Carton UPC# | 037332127280 |
| PHYSICAL | |
| Color | Orange & Yellow |
| Style | Fiber Optic |
| CONNECTIONS | |
| Connector A |  LC |
| Connector B |  ST |
| Number of Connectors | 4 |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

Related Items

Optional Products

| Related Model | Description | Qty. |
|--------------------------|---|------|
| N422-01M | 1M (3-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC) | 1 |
| N422-02M | 2M (6-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC) | 1 |
| N422-03M | 3M (10-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC) | 1 |
| N424-01M | 1M (3-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/LC) | 1 |
| N424-04M | 4M (13-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/LC) | 1 |
| N424-05M | 5M (16-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/LC) | 1 |
| N426-02M | 2M (6-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/SC) | 1 |
| N426-03M | 3M (10-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/SC) | 1 |
| N426-05M | 5M (16-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/SC) | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3515.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.