



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: P402-010

10-ft. Serial Modem Gold Cable, DB25F to DB25M

Highlights

- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration



Description

10 foot PC serial modem cable. DB25 female to DB25 male. Superior molded cables with built-in strain relief ensures the cable will last a very long time. Foil-shielding provide maximum EMI/RFI protection. Gold plated connectors and gold plated copper contacts offer superior conductivity. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- External modem with a Female DB25 port.
- Computer with an available DB25 serial port

Package Includes

- 10-ft. Serial Modem Gold Cable DB25F to DB25M


Features

- Superior molded cables with built-in strain relief ensures cable will last a very long time
- Foil-shielding provide maximum EMI/RFI protection
- Gold plated connectors and gold plated copper contacts offer superior conductivity
- Pins 1 - 8, 20, 22
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

INPUT	
Cable Length (ft.)	10
UPC ASSIGNMENT	
Unit Carton UPC#	037332012180
CONNECTIONS	
Connector A	 DB25 (FEMALE)

Connector B



WARRANTY

**Product Warranty Period
(Worldwide)**

Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2247.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.