



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SRW9U

SmartRack 9U Wall-Mount Rack Enclosure Cabinet



Highlights

- Designed for IT and education environments where equipment needs to be secure and out of the way
- 9U with adjustable front vertical rackmount rails
- Locking, reversible front door and locking, removable side panels
- Fully assembled for quick installation
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance

Description

The SRW9U 9U Wall-Mount Rack Enclosure Cabinet is designed to integrate wall-mounting, easy equipment access, and cable management in IT network applications with limited floor space. Ventilated front door and side panels allow generous airflow to keep equipment operating safely. Adjustable rack rails with square mounting holes accommodate up to 9U of standard 19" rackmount equipment. Supports up to 200 lbs of equipment. A sturdy wall-mount bracket allows the cabinet to quickly be hung on the wall.

Applications

IT network environments with limited floor space and classrooms where equipment needs to be secure and out of the way of students.

Package Includes

- SRW9U Wallmount Rack Enclosure
- (18) M6 screws
- (18) M6 cage nuts
- (18) M6 washers
- (2) Keys
- Owner's Manual

Features

- 9U wall-mounted enclosure
- Adjustable mounting depths up to 17" by 2 front vertical rackmount rails
- Ventilated front door and side panels for increased airflow
- Locking, reversible front door
- Locking, removable side panels
- Fully assembled for quick installation
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance

Specifications

PHYSICAL	
Installed whole system maximum rack depth (inches)	16.5
Installed whole system maximum rack depth (cm)	41.9

Installed whole system minimum rack depth (inches)	3
Rack Height	9U
Shipping Dimensions (HWD/in)	22.6 x 26.4 x 20.5
Shipping Dimensions (HWD/cm)	57.40 x 67.06 x 52.07
Shipping weight (lbs)	38.4
Shipping weight (kg)	17.41
Unit Dimensions (in.)	19.88 x 23.63 x 17.78
Unit weight (lbs)	35
Unit weight (kg)	15.875
Unit Dimensions (cm)	50.49 x 60.02 x 45.16
Color	Black
Style	Wall Mounted
Weight Capacity - Stationary (lbs)	200
Weight Capacity - Stationary (kg)	90.7
Cable Access Hole Measurement (inches)	9.812 x 2.35 (l x w)
SPECIAL FEATURES	
Grounding lug	Front and Back door frames
CERTIFICATIONS	
Certifications	EIA-310-E
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
SRFANWM	Wall-Mount Roof Fan Kit, 120V (2 high-performance fans; 5-15P plug)	1
SRCABLEDUCT1U	1U Horizontal Cable Manager (Finger duct with cover.)	1
SRCABLERING1U	1U Horizontal Cable Manager (Flexible ring type.)	1
SRSHELF2P1U	1U Cantilever Fixed Shelf (40 lb / 18 kg capacity; 12-in. / 305 mm depth.)	1
SRSWITCH	Magnetic Door Switch Kit for front and rear doors; requires ENVIROSENSE	1
SRCAGENUTS	Square Hole Hardware Kit (Includes 50 M6 screws and washers.)	1

SRCASTER	Heavy-Duty Rolling Caster Kit (Includes 4 casters)	1
UPSHDEARKIT	Heavy-Duty Mounting Ear Kit - Supports 2U cabinets up to 65 lb / 29 kg from front vertical rails in 4-post or 2-post racks and enclosures.)	1
N252-012	12-Port Cat6 Patch Panel 568B, 1U	1
N252-048	48-Port Cat6 Patch Panel 568B	1
SRCABLEDUCT1UHD	1U High Capacity Horizontal Cable Manager (Finger duct with dual-hinge cover)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4895.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.