



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SR4POST1224

45U 4-Post SmartRack Open Frame Rack - Thread (12-24) Mounting Holes



Highlights

- 45U 4-post open frame rack
- Black steel with threaded (12-24) mounted holes
- Toolless button holes to accept PDUs or cable managers

Description

SmartRack 4-post open frame racks are ideal for cost conscious 19 inch rack mount applications. Multiple units can be bolted together side by side.

Package Includes

- SR4POST1224
- Installation hardware
- 50x pieces of 12-24 screws and washers
- Cable management hooks
- Owner's Manual with warranty information

Features

- Supports 1000lbs of rackmount equipment
- Adjustable mounting depth (22 to 39 inches)
- Textured powder coat finish
- Heavy-duty cold-rolled steel construction
- Numbered mounting positions
- Bolt down provisions
- Threaded 12-24 holes
- Black finish
- Easy assembly

Specifications

PHYSICAL	
Installed whole system maximum rack depth (inches)	39
Installed whole system maximum rack depth (cm)	99.06
Installed whole system minimum rack depth (inches)	22

Installed whole system minimum rack depth (cm)	55.88
Rack Height	45U
Shipping Dimensions (HWD/in)	85 x 6 x 4
Shipping Dimensions (HWD/cm)	215.9 x 15.24 x 10.16
Shipping weight (lbs)	70
Shipping weight (kg)	31.5
Unit Dimensions (in.)	84.3 x 20.3 x 22-39.4 (depth adjustable)
Unit weight (lbs)	69
Unit weight (kg)	31.29
Unit Dimensions (cm)	214.12 x 51.56 x 55.9~100.1 (depth adjustable)
Color	Black
Style	4-Post
Weight Capacity - Stationary (lbs)	1000
Weight Capacity - Stationary (kg)	453.6
SPECIAL FEATURES	
Grounding lug	Includes a set of screws, bolts, and washers to secure a user-supplied grounding wire to Front and Back frames
CERTIFICATIONS	
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	EIA-310-D, IEC 60297-3-100, DIN 41494, RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
SRSCREWS	Threaded hole hardware kit - 50 each #12-24 screws	1
SRCABLEDUCTVRT	6-ft. (1.8 m) Vertical Cable Manager (Double finger duct with cover; toolless mounting.)	1
SRCABLEVRT3	3" Wide High Capacity Vertical Cable Manager (Double finger duct; toolless mounting.)	1
SRCABLEVRT6	6" Wide High Capacity Vertical Cable Manager (Double finger duct with cover; toolless mounting.)	1
SRCABLEVRT12	12" Width High Capacity Vertical Cable Manager (Double finger duct with cover; toolless mounting.)	1
SRCABLERINGVRT	6-ft. (1.8 m) Vertical Cable Manager (Flexible ring type; toolless mounting.)	1
SRCABLEDUCT1U	1U Horizontal Cable Manager (Finger duct with cover.)	1

SRCABLEDUCT1UHD	1U High Capacity Horizontal Cable Manager (Finger duct with dual-hinge cover)	1
SRCABLEDUCT2UHD	2U High Capacity Horizontal Cable Manager (Finger duct with dual-hinge cover)	1
B020-U08-19-IP	Console KVM Switch - 8-Port NetDirector 1U Rackmount Console IP KVM Switch w/19" LCD	1
SRCABLELADDER	10-ft. x 1-ft. (3 m x 0.3 m) Cable Ladder (Includes 2 sections; requires SRCABLETRAY or SRLADDERATTACH)	1
B040-008-19	NetController 19" VGA Console KVM Switch - 8 Port	1
N252-024	24-Port Cat6 Patch Panel 568B, 1U	1
B021-000-17	Rackmount Console - 1U Rackmount Console with 17" LCD	1
B040-016-19	NetController 19" VGA Console KVM Switch - 16 Port	1
N252-048	48-Port Cat6 Patch Panel 568B	1
B021-000-19	Rackmount Console - 1U Rackmount Console with 19" LCD	1
N252-012	12-Port Cat6 Patch Panel 568B, 1U	1
SRBOLTDOWN	Bolt-Down Kit (Secures included stabilizing brackets or optional stabilizing plates to facility floor.)	1
SRCABLERING1U	1U Horizontal Cable Manager (Flexible ring type.)	1
SRCABLERING2U	2U Horizontal Cable Manager (Flexible ring type.)	1
SRCASTER	Heavy-Duty Rolling Caster Kit (Includes 4 casters)	1
SRFAN3U	3U Fan Panel, 120V (3 high-performance fans; 210 CFM; 5-15P plug.)	1
SRSHELF2P	2U Cantilever Fixed Shelf (60 lb / 27 kg capacity; 18-in. / 457 mm depth.)	1
SRSHELF4PHD	Heavy-Duty Fixed Shelf (250 lb / 113 kg capacity; 26 in / 660 mm depth.)	1
SRSHELF4PKYBD	Keyboard Shelf (25 lb / 11 kg capacity; 16-in. / 406 mm depth.)	1
SRSHELF4PSL	Standard Sliding Shelf (50lb / 23 kg capacity; 28 1/4 in/ 660 mm depth.)	1
SRSHELF4PSLHD	Heavy-Duty Sliding Shelf (200 lb / 91 kg capacity; 26 in / 660 mm depth.)	1
SRXFAN3U	3U Fan Panel, 230V (3 high-performance fans; 315 CFM; C14 inlet.)	1
UPSHDEARKIT	Heavy-Duty Mounting Ear Kit - Supports 2U cabinets up to 65 lb / 29 kg from front vertical rails in 4-post or 2-post racks and enclosures.)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4943.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.